ThinkPad T460 Platform Specifications

Processor	6th Genera	ation Ir	ntel® Cor	e™ i3 / i5 /	i7 Process	or (i7-6	500U for discr	ete models only)	Smart card reader Optional: Smart card reader		
	Processor # of # of Base Max Turbo Cache Memory Processor								Media reader 4-in-1 reader (MMC, SD, SDHC, SDXC) Ports 4-in-1 reader (MMC, SD, SDHC, SDXC) Three USB 3.0 (one Always On), MiniDP, HDMI, Ethernet (RJ-45), Dock connector		
	Number i3-6100U	Cores	Threads	Frequency 2.3 GHz	Frequency	3MB	Types	Graphics		WiGig dock, coexists with WWAN (WE only)	
	i5-6200U		-	2.3 GHz	2.8 GHz	3MB			Camera (optional)HD720p resolution, low light sensitive, fixed focus	
	i5-6300U	2	4	2.4 GHz	3.0 GHz		DDR3L-1600	Intel HD graphics 520	Audio support	HD Audio, Realtek® ALC3245 codec / stereo speakers, 2W x 2 /	
	i7-6500U			2.5 GHz	3.1 GHz	4MB		520		dual array microphone, combo audio/microphone jack 6-row, spill-resistant, multimedia Fn keys, optional LED backlight	
	i7-6600U			2.6 GHz	3.4 GHz	4MB			Keyboard UltraNav™	TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad	
Graphics	Intel HD Graphics 520 in processor only, or Intel HD Graphics 520 in processor and NVIDIA GeForce® 940MX, 2GB memory (discrete graphics is only available in US); supports external digital monitor via HDMI or Mini DisplayPort; supports three independent displays; Max resolution: 3840x2160@60Hz (DisplayPort via Mini DisplayPort cable); 1920x1080@60Hz (HDMI)							•	l — • · · · · · · · · · · · · · · · · · ·	Power-on password, hard disk password, supervisor password, security keyhole Discrete TPM 1.2 TCG Certified and Firmware TPM 2.0 integrated in chipset Delivers improved thermal and power efficiency, up to 30 day standby, faster resume time, enhanced security, as well as anti-tampering measures Intel vPro Technology roptional: Swipe style fingerprint reader on the keyboard bezel	
Chipset	Intel SoC (System on Chip) platform								Internal battery Optional: Integrated Li-Ion or Li-Polymer 3-cell (23Wh) External battery Li-Ion 3-cell (23Wh) or 6-cell (48Wh or 72Wh)		
Memory	32GB max ⁷ / PC3-12800 1600MHz DDR3L, non-parity, dual-channel capable, two DDR3L SO-DIMM sockets								Max battery life	Models 6-cell 48Wh 6-cell 72Wh 3 + 3-cell 3 + 6-cell 48Wh 3 + 6-cell 72Wh	
Display							D backlight,		(MobileMark® 2014)	Integrated model	
Display				pect ratio, 3						discrete model 10.5 hr 15 hr 10.1 hr 14.7 hr 19.7 hr	
							_ED backlig		AC adapter	45W or 65W Slim AC adapter	
Multi-touch (opt)	250 nits, 16:9 aspect ratio, 700:1 contrast ratio, 160° viewing angle In-cell touch, supports 10-finger gesture, 250 nits								Preload	Windows 7 Professional 64 preinstalled through downgrade rights in Windows 10 Pro 64 • Lenovo Solution Center • ThinkVantage Product Recovery • Rescue and Recovery™ • ThinkVantage System Update • Adobe® Reader® Windows 10 Pro 64 • Lenovo Solution Center	
Storage	Some: SSD / SATA 6.0Gb/s (e.g. xxxG SSD) Some: SSD / PCle NVMe, PCle 3.0 x 2, 16Gb/s (e.g. xxxG SSD PCle NVMe) Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm or 9.5mm high, Shock Mounted Hard Drive, Active Protection System™ Some: SSHD with 8GB NAND flash memory (WE only)							PCIe NVMe)			
Optical	None								-	Microsoft® Office preloaded;	
Ethernet		Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) vPro model: Intel Ethernet Connection I219-LM (Jacksonville) • McAfee® LiveSafe™ (30-day trial)									
WLAN⁴ Bluetooth™	One of the following, configurable by model (WiGig can coexist with WWAN): • 11ac+BT, Broadcom BCM4356, 2x2, M.2 card • 11ac+BT, Intel Dual Band Wireless-AC 8260, 2x2, M.2 card • WiGig™+11ac+BT, Intel Tri-Band Wireless-AC 18260, 2x2 WLAN, WiGig, M.2 card Bluetooth 4.1 wireless, integrated in Wi-Fi + Bluetooth combo adapter							, WiGig, M.2 card pter		 One of the following, configurable by model: 1-year depot repair service 3-year/1-yr battery depot repair service 3-year/1-yr battery limited onsite service²⁴ 3-year/1-yr battery limited onsite service, OID (Onsite International Delivery)	
WWAN (optional)	al) One of the following, configurable by model (WWAN can coexist with WiGig): • Wireless WAN upgradable						ist with WiGig	ı):	Mil-Spec test	MIL-STD-810G military certification	
OlM cond (cod)	 Wireless WAN Upgradable Wireless WAN, Sierra Wireless EM7455, Qualcomm® 4G LTE-Advanced/DC-HSPA+/HSPA+/HSPA/UMTS/GNSS, M.2 card Wireless WAN, HUAWEI ME906S, HUAWEI 4G LTE/WCDMA/HSPA/GSM/GPRS/EDGE/GNSS, M.2 card (WE only) Micro-SIM card slot, optional Verizon LTE (US) or Lenovo Connect (WE) SIM card 							2 card (WE only)	Environment	EPEAT™ Gold (US only); ENERGY STAR® 6.1; GREENGUARD®; RoHS-compliant	
SIM card (opt) Dimensions ³	WxDxH:							(VVE) SIIVI Card	-		
Weight ²	WxDxH: 13.35" x 9.15" x 0.83"; 339mm x 232.5mm x 21mm Models No + 6-cell 3-cell + 3-cell 3-cell + 6-cell							3-cell + 6-cell			
3	Integrated N	Von-tou	ch 3	3.84 lb / 1.74		.82 lb / 1.		1.13 lb / 1.87 kg			
	Integrated N		_	3.91 lb / 1.77		88 lb / 1.		1.20 lb / 1.90 kg			
	Discrete No			3.86 lb / 1.75		90 lb / 1.		1.22 lb / 1.91 kg			
	Discrete Mu			3.93 lb / 1.78	kg 3.	97 lb / 1.	80 kg 2	1.28 lb / 1.94 kg			
Case material	Glass-Fibe	er Rein	forced P	Plastic							