

PREMIUM QUALITY POSTERS WITHOUT THE PREMIUM COSTS

The opportunities are endless
imagePROGRAF iPF8400SE



The imagePROGRAF iPF8400SE empowers you to have on-the-spot posters that brings your creative ideas to life, in volume, as and when you need to.

Designed ultimately for poster printing, the iPF8400SE is packaged with our powerful PosterArtist Lite* software. A solution that allows you to, quickly and easily, produce a wide range of posters for various purposes, in four easy steps.

The iPF8400SE makes full use of Canon's unique LUCIA-EX ink system. An ink type with proven strengths in colour reproduction.

The iPF8400SE will allow you to turn around your creative ideas in record time. You can create and replace your posters quickly and easily as many times as you want, with minimal cost. Ensure your marketing remains relevant, fresh and always eye-catching.

At a glance

- 44 inch
- 2400 x 1200 dpi
- 6 colour LUCIA EX ink
- Borderless printing
- A0 Plain paper in 56 seconds
- B0 Size prints
- Broad media selection

Request your free 30 day trial of PosterArtist today from wide-format@canon.com.au



High Capacity Ink Tanks

Optional 700ml ink tanks for greater productivity and less ink changes



LUCIA EX ink system

LUCIA EX ink offers long-lasting prints, that resists fading over time



"Hot" Swap

Change ink tanks without pausing your print job



Accounting Manager

Software helps keep track of printing costs



PosterArtist Lite

Print multiple formats with a simple "drag and drop" process with our Direct Print & Share Utility



Red Ink Tank

Ensure vivid reds and oranges with the included Red Ink tank

*Upgradable to PosterArtist

Canon

no one sees print like you

imagePROGRAF iPF8400SE

product specifications

MAIN UNIT

Print head	PF-05 (1 printhead installed)
Technology	FINE (Full-Photolithography Inkjet Nozzle Engineering)
Print Resolution (Max)	Up to 2400 × 1200 dpi
Ink Type	LUCIA EX Ink (Pigment-based)
Ink tank	330ml: PFI-306 BK/MBK/C/M/Y/R 700ml: PFI-706 BK/MBK/C/M/Y/R
Colours	Black, Matte Black, Cyan, Magenta, Yellow, Red
Ink tank shipped with Printer	6 Colours (full 330ml each colour)
Printer Memory	384 mb
Power supply	AC 100 - 240 V (50 - 60 Hz)
Power Consumption	Maximum 190W or Less Standby (100-120V) 5 W or Less Power Off 0.5W or Less (compliant with executive order)
Certifications	International Energy Star Program (WW), RoHS directive
Operation Environment	Temperature 15 – 30°C (59 – 86°F) Relative Humidity 10 – 80% (No Condensation)
Dimensions with Stand (HxWxD)	1,144 x 1,893 x 734
Weight	117 kg
User replaceable items	Print-Head (PF-05) Maintenance Cartridge (MC-08) Cutter Blade (CT-06)

MEDIA SPECIFICATIONS

Media Feed	Roll Paper - Front-loading Roll Feed One Roll, Front Output Cut Sheet Manual Feed One Sheet - Front-loading, Front Output
Media Width	Roll Paper 254 - 1,117.6 mm *Formal supported "Media Width" is limited to the "Media Size" (roll paper widths) Cut Sheet - 203.2 - 1,117.6 mm
Minimum media Length	203.22 mm (Cut Sheet and Roll)
Maximum print length	Roll Paper 18 m (Varies according to the OS and application) Cut Sheet Manual Feed from Top 1.6 m
Borderless printing widths (Roll Media only)	515 mm (JIS B2), 1,030 mm (JIS B0), 594 mm (ISO A1), 841 mm (ISO A0), 10", 14", 17", 24", 36", 42", 44"
Printer stand	Standard
Media Thickness	0.07 mm - 0.8 mm (Cut Sheet and Roll)
Media Cores Sizes	2" and 3" Core (Adapter Included)
Printable margins	Manual Feed (Front) Leading and Left/Right Edges: 5 mm (0.20") Trailing Edge: 23 mm (0.90") Roll Feed All Sides: 5 mm (0.20") or 0" for Borderless
Maximum media roll outer diameter	150 mm
Acoustic Noise	Operation: 50 dB or less



SOFTWARE SPECIFICATIONS

Printing Software	Canon Printer Driver, Print Plug-in for Photoshop, **Print Plug-in for DPP, ***Printer Driver Extra Kit (Free Layout, imageRUNNER Linking Function), Print Plug-in for Microsoft Office
Applications	PosterArtist Lite with Poster Solutions (PC only)
Utilities	imagePROGRAF Status Monitor (Windows), Print Monitor (Macintosh), Media Configuration Tool, Remote UI, Accounting Manager
Printer Language	GARO (Graphic Arts language with Raster Operations)
Operating System [^]	Windows XP (32/64-bit), Server 2003 (32/64-bit), Server 2008 (32/64-bit), Windows Vista™ (32/64-bit), Windows 7 (32/64-bit); Macintosh™ OS X 10.5.8 - 10.7x
Interface	Standard USB 2.0 High-Speed 10/100/1000 Base - T/TX

OPTIONS/ACCESSORIES

Roll Holder Set RH2-44
PosterArtist (PC only)

- * The maximum printable length varies depending on the application, OS, and RIP used. The maximum printable length from Canon Printer Driver is 50 feet.
- ** For Adobe Photoshop 6, 7, CS, CS2, CS3, CS4, CS5, running on Windows 2000/XP/ Windows Vista (32 bit)/Windows 7 or Macintosh OS X 10.2/10.3/10.4/10.5/10.6/10.7.
- *** For Digital Photo Professional version 2.1 or later running on Windows 2000/XP/Windows Vista (32 bit)/Windows 7 or Macintosh OS X 10.2/10.3/10.4/10.5/10.6.
- [^] For imagePROGRAF Printer Driver. For printing from PostScr[®]ip applications such as Adobe Illustrator[®] or QuarkXPress[®], please use a PostScript compatible RIP package. For a list of Canon recommended RIP packages, please contact Canon Australia on 13 13 83.



Australia: call 1800 444 199 or visit canon.com.au

New Zealand: call 0800 222 666 or visit canon.co.nz

