

Canon imagePROGRAF iPF9400S

Exquisite image quality for the most demanding of jobs

The imagePROGRAF iPF9400S Large Format printer for commercial photography, production, proofing and signage.

The iPF9400S delivers the performance and versatility you need to produce profitable, high-quality output in less time.

With low running costs, enhanced colour matching tools and faster speeds, the iPF9400S would be a welcome introduction into any busy environment.

At a glance

- 60 inch
- 2400 X 1200dpi
- Take-up unit for long print runs
- 8 colour LUCIA-EX ink
- 250GB hard drive
- Gallery wrap
- Borderless printing
- Media Configuration Tool



Colour Density Sensor

Stable output from month to month



Calibration Link

Consistent image quality across the Canon 12-colour imagePROGRAF range from 24" to 60"



LUCIA EX ink system

Improved colour output and scratch resistance with reduced bronzing



Sub-ink tank system

Ink can be changed without interrupting a print job



Accounting Manager

Software helps keep track of printing costs



imagePROGRAF

Achieve more. Beyond technology.

Canon

imagePROGRAF iPF9400S product specifications



Main Unit

Print-Head	PF-05 (2)	
Technology	FINE (Full-Photolithography Inkjet Nozzle Engineering)	
Print Resolution (Max.)	Up to 2400 × 1200 dpi	
Ink Type	LUCIA EX Ink (Pigment-based)	
Ink Tank	PFI-306 (330ml): BK, MBK, C, M, Y, PC, PM, GY PFI-706 (700ml): BK, MBK, C, M, Y, PC, PM, GY	
Colours	Cyan, Photo Cyan, Magenta, Photo Magenta, Yellow, Black, Matte Black, Gray	
Ink Tank Shipped with Printer	8 Colours (Full 330ml Each Colour)	
Hard Disk Capacity	250GB	
Printer Memory	640MB	
Power Supply	AC 100-240V (50-60Hz)	
Power Consumption	Maximum Standby (220-240V) Power Off	190W or Less 6W or Less 0.5W or Less (compliant with executive order)
Certifications	UL, FCC Class B, ENERGY STAR®	
Operational Environment	Temperature Relative Humidity	15 – 30°C (59 – 86°F) 10 – 80% (No Condensation)
Dimensions with Stand (H x W x D)	1143 x 2298 x 767mm	
Weight	Approx. 161kg	
User-Replaceable Items	Print-Head (PF-05) Maintenance Cartridge (MC-08) Durable Rotary Media Cutter (CT-06)	

Media Specifications

Media Feed	Front-loading Roll Feed Front-loading Manual Feed	One Roll, Front Output One Sheet, Front Output
Media Width	Cut Sheet Roll Feed	8" – 60" (203 - 1524mm) 10" – 60" (254 - 1524mm)
Minimum Media Length	8" (203mm)	
Maximum Print Length	Manual Feed Roll Feed	1.6m 18m*
Borderless Printing Widths (Roll Media Only)	10"/14"/17"/24"/36"/42"/44"/50"/60"/ B2 [20.28"(565mm)]/A1 [23.38"(594mm)]/ A0 [33.11"/841mm]/B0 [40.55"(1030mm)]	
Printer Stand	Standard	
Media Thickness	0.07mm-0.8mm	
Media Core Sizes	2" or 3" Core (with Supplied Adapter)	
Printable Margins	Manual Feed (Top/Front) Leading and Left/Right Edges: 5mm (0.20") Trailing Edge: 23mm (0.90") Roll Feed All Sides: 5mm (0.20") or 0" for Borderless	
Maximum Media Roll Outer Diameter	150mm (5.9")	
Acoustic Noise	Operation 68dB or Less	

Software Specifications

Printing Software	Canon Printer Driver, Print Plug-in for Photoshop,** Print Plug-in for DPP,** Printer Driver Extra Kit (Free Layout, imageRUNNER® Linking Function), Print Plug-in for Microsoft Office (PC only)
Applications	PosterArtist Lite (PC only)
Utilities	imagePROGRAF Status Monitor (Windows®), Print Monitor (Macintosh®), Media Configuration Tool, Remote UI, Accounting Manager (PC only), CMCC
Printer Language	GARO (Canon Proprietary)
Operating System[^]	Windows XP (32/64-bit), Server 2003 (32/64-bit), Server 2008 (32/64-bit), Windows Vista (32/64-bit), Windows 7 (32/64-bit); Macintosh OS X 10.5.8-10.7.x
Interface	Standard USB 2.0 High-Speed 10/100/1000Base-T/TX

Options/Accessories

Options	Roll Holder Set RH2-6 Basket BU-01 PosterArtist (PC only)
----------------	---

* The maximum printable length varies depending on the application, OS, and RIP used. The maximum printable length from Canon Printer Driver is 50 feet.

** For Adobe® Photoshop® CS3 (32bit), CS4, CS5 running on Windows XP/Server 2003/Server 2008/Windows Vista/ Windows 7 or Macintosh OS X10.4.11-10.6.

*** For Digital Photo Professional version 2.1 or later running on Windows XP/Server 2003/Server 2008/Windows Vista/Windows 7 or Macintosh OS X10.4.11-10.6.

[^] F or imagePROGRAF Printer Driver. For printing from PostScript applications such as Adobe Illustrator® or QuarkXPress®, please use a PostScript compatible RIP package. For a list of Canon recommended RIP packages, please contact Canon Australia on 13 13 83.



Australia: call 1800 444 199 or visit canon.com.au

New Zealand: call 0800 222 666 or visit canon.co.nz



Achieve more. Beyond technology.