



## Microline Dot Matrix Printer

### ML1120 9-Pin Dot Matrix Printer

**A low cost, high volume 9-pin printer with proven reliability.**

Small in size, these incredibly reliable dot matrix printers give you all the compatibility of the leading competition, but with the added reassurance of OKI Printing Solutions' renowned reliability in the SIDM market. Perfect for businesses that demand value for money, but don't want to compromise on price or performance.

#### Highlights:

- Affordable printing solution
- 4 million character ribbon life
- 9-pin print head with OKI Printing Solutions reliability
- Up to 330 characters per second print speed
- High duty cycle and low maintenance means more productivity
- 10% faster than the leading competitors
- Zero Tear Capability prevents waste
- USB as standard for even more flexibility



# ML1120

		ML1120
<b>General</b>	Number of pins	9
	No. of multi-part forms	5 (one original + 4 copies)
<b>Speed and throughput</b>	Super speed draft (12cpi only)	375cps
	High speed draft (all cpi)	333cps
	Utility (all cpi)	250cps
	Near letter quality (all cpi)	62.5cps
	Fastest print speed	375cps
<b>Font &amp; print features</b>	Carriage width (10cpi)	80 columns
	Max. in compressed mode	160 columns
	Character pitch	10/12/15/17.1/20 pitch
	Graphics resolution	Up to 240 x 216 dpi
	Typeface & Font	Utility, High Speed Draft, Super Speed Draft, NLQ, Barcodes
	Typestyle	Emphasised, Enhanced, Double Width, Italics
<b>Emulations &amp; Interfaces</b>	Printer emulations	Epson LX, IBM Graphics or Oki Microline
	Standard interfaces	Centronics Parallel, USB 2.0, Serial RS232
	Optional interfaces	N/A
<b>Paper handling</b>	Continuous paper	76.2 – 254mm
	First printable line (from top of page)	Cut sheet: 2.12mm (to centre of character) Continuous: 2.12mm (to centre of character)
	Standard	Automatic sheet loading, Short paper tear-off, Auto park feature
	Paper feed	Top/Rear/Bottom path, Rear push tractor, top pull tractor, friction fed cut sheet
<b>Physical</b>	Dimensions (HxWxD)	150 x 349 x 232mm
	Weight	4.2kg
	Memory	64KB
	Noise level	53dB(A) (ISO 7779)
<b>Power</b>	Power requirements	220V–240V AC
	Frequency	50/60Hz
<b>Reliability</b>	Print head life	400M strokes/wire
	Ribbon life	4 million characters
	MTBF	10,000 hours

**Consumables Information:** Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

## OKI DATA AUSTRALIA

146 O'Riordan Street  
 Mascot NSW 2020  
 T (02) 9667 7240  
 F (02) 9667 7333  
 WWW.OKI.COM.AU



As an ENERGY STAR Partner, Oki has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

**OKI**  
 PRINTING SOLUTIONS