HP Color LaserJet Pro MFP M277 Series



A compact MFP loaded with productivity features that's ready to fit right in and get to work.

You'd never expect this much performance from such a small package. This loaded MFP and Original HP Toner cartridges with JetIntelligence combine to give you the tools you need to get the job done.



HP Color LaserJet Pro MFP M277n



HP Color LaserJet Pro MFP M277dw

Accomplish more with your time

- Create professional-quality colour documents, and speed through tasks with super-fast two-sided printing.¹
- Choose the MFP that's the smallest in its class, and prints from sleep mode faster than comparable devices.¹
- Access time-saving apps from the 3-inch (7.6 cm) touchscreen, and scan directly to email and the cloud.²
- Easily print Microsoft® Word and PowerPoint® documents—now directly from your USB drive.⁸

Easy mobile printing options

- Print to this MFP with just a touch of your NFC-enabled mobile device—no network needed.⁴
- Count on wireless direct printing in the office—from mobile devices—without accessing the company network.⁵
- Easily print from a variety of smartphones and tablets—generally no setup or apps required.³

More pages, performance, and protection

- Get more pages than ever before—using Original HP High-Yield Colour Toner cartridges with JetIntelligence.⁷
- Count on professional quality at high speeds—HP ColorSphere 3 toner works best with your HP printer.
- Get the authentic HP quality you paid for with anti-fraud technology.
- Print right away with preinstalled toner cartridges. Replace them with optional high-yield cartridges.⁹

Meet everyday IT challenges head-on

- Safeguard data and easily manage devices with a suite of essential security and management features.
- Easily access, print, and share resources with Ethernet and wireless networking.⁶
- Increase security, restore control, and help avoid additional expenses—with HP JetAdvantage Private Print.¹⁰
- Protect your investment with HP Care Pack. Let our HP certified engineers resolve all your technical issues.¹¹

¹Comparison based on manufacturers' published specifications (as of November 2014) and includes colour laser multifunction printers (MFPs) with print speed between 11 and 20 pages per minute (ppm). ² Requires a wireless access point and an Internet connection to the printer. Services require registration. App availability varies by country, language, and agreements. For details, visit hpconnected.com ³ Local printing requires mobile device and printer to be on the same wireless network or have a direct wireless connection. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP Web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See hp.com/go/mobileprinting for more details. Some features require purchase of optional module. ⁴ Feature is only available for the HP Color LaserJet Pro M277dw. Mobile device must support near-field communications (NFC)-enabled printing. For more information, see hp.com/go/mobileprinting 5 reature is only available for the HP Color LaserJet Pro M277dw. Mobile device must be connected directly to the printer's wireless network prior to printing. Depending on mobile device, an app or driver may also be required. Wireless performance is dependent on physical environment and distance from the access point, and may be limited during active VPN connected directly to the printer's wireless network prior to printing. Depending on mobile device, an app or driver may also be required. Wireless performance is dependent on physical environment and distance from access point, and may be limited during active VPN connected directly to the printer's wireless network prior to printing. Depending on mobile device, an app or driver may limited du

Product walkaround

- 1 Intuitive 7.6 cm (3-inch) colour touchscreen tilts for easier viewing while sitting or standing
- 2 50-sheet automatic document feeder (ADF)
- Flatbed scanner handles up to 216 x 356 mm paper
- 4 100-sheet output bin
- 5 Built-in wireless direct/NFC touch-to-print
- 6 Output bin extension
- 7 Power on/off button
- 8 Built-in automatic two-sided printing
- 9 Easy-access USB port for printing and scanning without a computer
- 10 Front door access to Original HP Toner cartridges with JetIntelligence
- 11 Single-sheet priority feed slot
- 12 150-sheet main input tray 2
- 13 Hi-Speed USB 2.0 printing port
- 14 Fast Ethernet 10/100/1000 Base-TX network port
- 15 800 MHz processor, 256 MB RAM
- 16 Built-in wireless networking
- 17 Fax "line in" port
- 18 Telephone "line out" port
- 19 Rear door (provides access to paper paths)

HP Color LaserJet Pro MFP M277dw shown





Series at a glance





Model	HP Color LaserJet Pro MFP M277n	HP Color LaserJet Pro MFP M277dw
Product number	B3Q10A	B3Q11A
Functions	Print, copy, scan, and fax	Print, copy, scan, and fax
Print speed (black and colour)	Up to 18 pages per minute (ppm), A4	Up to 18 ppm, A4
Automatic two-sided printing	Not available	✓
Networking	Gigabit Ethernet	Gigabit Ethernet, wireless 802.11b/g/n
Mobile printing capability	HP ePrint, Apple AirPrint, Mopria-certified	NFC touch-to-print, wireless direct printing, HP ePrint, Apple AirPrint, Mopria-certified

HP Services

Downtime can have serious consequences, so HP provides support beyond the standard warranty. You benefit from reduced risk, maximized uptime, predictable service delivery and no unbudgeted repair costs.

Choose from:

Optimized Care (optimum performance and stability): 4 hour Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Standard Care (high level of uptime): \mbox{Next}

Business Day Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Basic Care (minimum recommended support): Next Business Day Onsite Support

4 hr Onsite Support: Onsite support within four hours after a service call received within the coverage window

Next Business Day Onsite Support: Onsite service the next business day after the service call is received

Maintenance Kit Replacement Service:

Onsite replacement of your printer's maintenance kit including parts, materials, and labor

Installation with Network Configuration

Service: Assembly, network configuration, and basic administrator familiarization

For more information about HP Care Pack, HP Contractual, or HP Managed Print Services, visit hp.com/go/printservices



















Top Features

Speed through tasks, using a wide range of productivity and workflow features—while consistently producing professional-quality prints. This loaded MFP gives you the tools you need to get the job done quickly.

Stay on top of pressing business demands—whether you're in the office or on the go. ¹ HP's wide range of mobile printing features let you work securely from wherever business takes you. ¹

Bring out the best in your MFP. Get more high-quality pages than ever, using Original HP Toner cartridges with JetIntelligence.² Help ensure peak printing performance, and get the authentic HP quality you paid for—unmatched by the competition.

Seamlessly manage the flow of information to and from your devices, using innovative HP JetAdvantage business workflow and printing solutions. Increase MFP and data security, and stay connected to your work with wired and wireless capabilities.³

Product	
B3Q10A	HP Color LaserJet Pro MFP M277n
B3Q11A	HP Color LaserJet Pro MFP M277dw
Accessories	
C6520A	HP USB 2.0 printer cable (a-b), 3 meter
Q6264A	HP Hi-Speed USB printer cable, 1.8 m (6 ft)
Supplies ³	
CF400A	HP 201A Black Original LaserJet Toner Cartridge (~1,500 pages)
CF400X	HP 201X High Yield Black Original LaserJet Toner Cartridge (~2,800 pages)
CF401A	HP 201A Cyan Original LaserJet Toner Cartridge (~1,400 pages)
CF401X	HP 201X High Yield Cyan Original LaserJet Toner Cartridge (~2,300 pages)
CF402A	HP 201A Yellow Original LaserJet Toner Cartridge (~1,400 pages)
CF402X	HP 201X High Yield Yellow Original LaserJet Toner Cartridge (~2,300 pages)
CF403A	HP 201A Magenta Original LaserJet Toner Cartridge (~1,400 pages)
CF403X	HP 201X High Yield Magenta Original LaserJet Toner Cartridge (~2,300 pages)

HP Care Packs

10/4255	1100
UX435E	HP 3-year Next Business Day Exchange Color LaserJet MFP-M SVC

UX449E HP 3-year Onsite Exchange Color LaserJet MFP-M SVC
UX444E HP 3-year Pickup Return Color LaserJet MFP-M SVC
UX439E HP 3-year Return Color LaserJet MFP-M SVC

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc

Pape

Contact HP via phone: Asia: 65 6253 8500

Solutions

HP Web Jetadmin: hp.com/go/wja
HP Universal Print Driver: hp.com/go/upd

HP Imaging and Printing Security Center: $\underline{\text{hp.com/go/ipsc}}$

¹ Local printing requires mobile device and printer to be on the same wireless network or have a direct wireless connection. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP Web-connected printer. App or software and HP ePrint account registration may also be requires broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See https://px.com/go/mobileprinting for more details. Some features require purchase of optional module. ² Based on cartridge yields for HP 131A compared with HP 201X Original HP Laser Jet Toner Cartridges. For more information, see https://px.com/go/learnaboutsupplies
³ Declared yield in accordance with ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details, see https://px.com/go/learnaboutsupplies

HP Color LaserJet Pro MFP M277 Series

Description	Technical specifications Functions	HP Color LaserJet Pro MFP M277n (B3Q10A)	HP Color LaserJet Pro MFP M277dw (B3Q11A)
Text per per general Biol Clamani, Mills per la gene Biol Cla		Print, cop	ry, ocarr, rax
The second Strategy Company of the C		Manual	Automatic (standard)
Tritispation The Charles of Section 19 to 19 t			
Anter transplaces Particle registery Particl			
Service Action before The Control of Contro			
Alter and promoters of the company o	Print technology	La	aser .
Protect management	Print resolutions	Black (best): Up to 600 dpi	; Colour (best): Up to 600 dpi
Peter state of pert language	Print resolution technologies		
Service of the Company of the Compan			
Interest Advantagement Interest Advantagement (Ling), Nationally (Ling) (Ling) (Applications) Interest Advantagement (Ling), Nationally (Ling) (Ling) (Applications) Construction (Ling), Nationally (Ling)			
Security			
Sean production (Sean Sean production (Sean Sean production (Sean Sean production (Sean Sean Sean Sean Sean Sean Sean Sean	Printer management		
Seat specified Chancel (by 1) (0 10 or 10		Security Center; HP Utility	y (Mac); HP Device Toolbox
Spear people	Scan		
Space (page 12) Space (pag	Scan type/technology	Type: Flathed ADE: Technolog	nav: Contact Image Sensor (CIS)
Palmarcel 100 300 300 400			
Sear test models Findings of the Company of the Co			
Formation can opport would find the following IP Sear software and one application van Trombin in this Comment of the following IP Sear and the sear application van Trombin in this Comment of the following IP Sear and the sear application van Trombin in this Comment of the following IP Sear and the search of the following IP Sear and the search of the following IP Sear and the search of the following IP Search of the following IP Search of the search of t			
Seat Bell	Scan size		
Black (sereal, All-Lib to 18 gene, Black (sereal, All-Lib to 18 gene)	Scan input modes	Front-panel scan, copy, e-mail, fax, or file buttons; HF	P Scan software; and user application via TWAIN or WIA
Copy series	Scan file format	PDE searchable PDE IPG	S. RTE TXT. BMP. PNG. TIFF
Copy segond Black (secretal, Age; to the figure, Black (secretal, Black (secretal)))); (b)		i bi, sedendo e i bi, se	3,111,111,511,1113,1111
Bit Clay Company Bit Clay Co			
Black (text & graphice): 100 x 420 dp (Fatherd, 200 x 300 dp (Fatherd, 200 dp (Fathe			
Men of closes Open resides Number of copies, Recommendation of the control of the	First copy out	Black (A4, ready): As fast as 13.5 sec	c; Colour (A4, ready): As fast as 16 sec
Men of closes Open resides Number of copies, Recommendation of the control of the	Copy resolution	Black (text & graphics): Up to 300 x 420 dpi: Colour (tex	tt & graphics): 300 x 420 dpi (Flatbed), 300 x 360 dpi (ADF)
Copies renting Number of copies. Pelicular Printings Lighter/Tables: (Partners Paper Mailt ages rops) cliented Tables (Capies centring) See a rend 15 6 18 10 10 10 10 10 10 10 10 10 10 10 10 10			
Number of capes, Nethod of Capes, Neth			
The speed 1			
Bisc (best): Up 1: 300 x 2000 do; Bisc		Number of copies; Reduce/Enlarge; Lighter/Darker; Optimize; Paper; Multi-page copy; Collation	n; Tray Select; Two-Sided; Draft Mode; Image Adjustment; Set as New Defaults; Restore Defaults
Exercision	Fax		
Exercision	Fax speed	33.6 kbps (maximum), 14.4 kbp	ps (default); 3 sec per page (letter)
Secure control (Additional Connectivity) Secured Connectivity He Speed (158 2 port Loutile Final Element 1 Element			
Connectivity			
Manual connections He Pelmin, Apple Am Prior** Morphise certified, Mobile prior, capability* Network capability* He Pelmin, Apple Am Prior**, Morphise certified, Mobile Pages Memority and Pages Memory		υριο 4	noo pages
Motion Composition Fig. 4 Pehrnst, Apple Air Printing A, Magra ceretified, Mobile Agos Fig. 4 Pehrnst, Apple Air Printing A, Agole Air Printing A, A			
Sendand butter Send	Standard connectivity	Hi-Speed USB 2.0 port; built-in Fast Ethernet	
Service (sepablish): No Service (sepablish	Mobile print capability ⁴	HP ePrint, Apple AirPrint™, Mopria-certified, Mobile Apps	HP ePrint, WiFi Direct Printing, Apple AirPrint™, Mopria-certified, Mobile Apps
Nemony Description No Description No Description Description No Description Desc	Network ready	Standard built-in Ethernet	Standard built-in Ethernet 802.11 b/g/n. WiEi operates as both an AP (with Wi-Fi Direct) and STA
Weekers (appelled) Bull-in 80.211 big/in. Autheritation via WEE WRAMPAC, et 80.21 tx. Encrypton via AES Memory 250.MB (WW) 150-Deep troubure. 250 to 2,500 page. 80.0102 Troubure (150-Deep troubure.) 150-Deep troubure. 250 to 2,500 page. 150-Deep troubure. 250 page. 150-Deep troubure. 250 to 2,500 page. 150-Deep troubure. 250 page. 250 page. 250 page. 250 pa			
Memory 19. 250 MB Daty cycle 19. 150-sheet input trax, multipurpose tay 100-sheet and trax, plant			
Memory Duty cycle Up to 30,000 pages; Recommended monthly page volume? 250 to 2,500 pages Processor speed	Wireless capability	No	
Duty cycle Processor speed 800 MHz Processor speed 150-sheet input tray, multipurpose tray 152 to 163 g/m² (Dateclosidas), part 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended, up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended, up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended, up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended (up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended (up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended (up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended (up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended (up to 175 g/m² Potacards, 200 g/m² PD detect do to 163 g/m² (Cateclosidas), commended (up to 175 g/m² Potacards, 200 g/m² PD detector, 200 g/m² PD detecto			
Processor speed Progrey handling Input ISO-Sheet Input Tay, multipurpose tray Output Progrey for Charles ISO-Sheet Input Tay, multipurpose tray ISO-Sheet Input Tay, multipurpose tray Output Progrey for Charles ISO-Sheet Input Tay, multipurpose tray ISO-Sheet Input Tay, multipurpose tray Output Progrey for Charles ISO-Sheet Input Tay Iso-Sheet I	Memory	256	6 MB
Processor speed Progrey handling Input ISO-Sheet Input Tay, multipurpose tray Output Progrey for Charles ISO-Sheet Input Tay, multipurpose tray ISO-Sheet Input Tay, multipurpose tray Output Progrey for Charles ISO-Sheet Input Tay, multipurpose tray ISO-Sheet Input Tay, multipurpose tray Output Progrey for Charles ISO-Sheet Input Tay Iso-Sheet I	Duty cycle	Up to 30,000 pages; Recommended mo	onthly page volume:5 250 to 2,500 pages
Paper Incolumn 150-sheet input tray, multipurpose tray 100-sheet input tray, multipurpose tray 100-sheet input tray, multipurpose tray 100-sheet input			
Decision 100-sheet injust tray 100-sheet injust tray 100-sheet on the property 100-sheet on the property tray 100-sheet on the property tray 100-sheet on the property 100-sheet on the prop		500) (H) (Z)
Media spe Paper (brochure, niejer, plain), photo paper (borderless, HP permitum, panors), bits bit), envelopes, labels, cards (greeting, index), transparencies			
Media byee			
Media sees custom Society Socie	Output	100-sheet output tray	
Media sees custom Society Socie	Media type	Paper (brochure inkiet plain) photo paper (borderless, HP premium paporamic plus tab), envelopes labels, cards (greeting index), transparencies	
Media yes sustom 76.2 x 127 to 215.9 x 355.6 mm (3 x 5 10 x 14 in) Mediph 76.2 x 127 to 215.9 x 355.6 mm (3 x 5 10 x 14 in) 420 x 417 x 322 mm (16.5 x 16.4 x 12.7 in) Mediph 76.2 x 127 to 215.9 x 355.6 mm (3 x 5 10 x 14 in) 420 x 417 x 322 mm (16.5 x 16.4 x 12.7 in) 420 x 417 x 322 mm (16.5 x 16.4 x 10.4			
Pinestans (W x x x x) 42(0 x 417 x 322 mm (16.5 x 15, 1x 122 m) 42(0 x 417 x 322 mm (16.5 x 16, 4 x 122 m)			
Windows Windows Or Sp. 22-bit, Windows Win 7 (Including State Edition 32-bit), Windows Windows Sp. 22-bit, Windows Win 8 Enterprise 9 bit, Windows Win 8 Enterprise 9 bit, Windows W	Media sizes custom		5.6 mm (3 x 5 to 5 x 14 in)
What's in the box IP Color Laser AP To MPE M277 (it (B3010A): IP 201A Black Original Laser NC Cartridge (-1,500 yield) and Introductory IP Laser let Color cartridges (-1,700 yield). Intalliance in the cartridge (-1,500 yield) printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord;	Dimensions (W x D x H)	420 x 384 x 322 mm (16.5 x 15.1 x 12.7 in)	420 x 417 x 322 mm (16.5 x 16.4 x 12.7 in)
What's in the box IP Color Laser AP To MPE M277 (it (B3010A): IP 201A Black Original Laser NC Cartridge (-1,500 yield) and Introductory IP Laser let Color cartridges (-1,700 yield). Intalliance in the cartridge (-1,500 yield) printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software on CD-ROM; Power software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord; USB cable (6 ft/1,8 m) Printer documentation and software cord; Power cord;	Weight	15 3 kg (33 7 lb)	16.3 kg (35.9 lb)
and Introductory HP Laser Jet Color cartridges (~700 colour composite (CY/MP) yelds, installation guide. Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software on CD-ROM, Power cord, USR cable (6 ft/1.8 m) Printer documentation and software cord. Printer documentation and software co			
Warranty features Systems	Wildt S III tile DOX		
Windows: Windows XP (SP3) 32-bit and 64-bit, Windows Win7 (Including Starter Edition 32-bit and 64-bit), Windows Win8 Basis: 62-bit, Windows W			
Systems Compatible operating systems Windows: Windows XP (SP3) 32-bit and 64-bit, Windows Win8 finetuning Starter Edition 32-bit and 64-bit, Windows Win8 Basic 64-bit, Windows Win8			
Mindows XM (1982) 32-bit, and 64-bit, Windows Win F Control (1982) 32-bit and 64-bit, Windows Win B Enterprise N 22-bit, Windows Win B Enterprise W 22-bit, Windows Win B Enterprise N 22-bit	Warranty features	One-year exch	hange warranty
Windows Win8 Basic 32-bit, Windows Win8 Pro 32-bit, Windows Win8 Enterprise 93-bit, Windows S N 10 Naveries, Mobile Operating Systems: 050, Android Windows 8 R FT, Other: Debian (5.0, 5.0.1, 5.0.2, 5.0.3) (supported by the automatic installer), Fedora (9, 9.0, 10, 10.0, 11.0, 11, 12, 12.0), HPUX 11 and Solaris 8/9, Linux (9.4, 9.5), Red Hat Enterprise I windows Win8 Enterprise 93-bit, Windows Win8 Enterprise 94-bit, Windows Win8 Enterprise 94	Systems		
32-bit, Windows Win8 Pro 32-bit, Windows Win8 Enterprise N 32-bit, Windows Win8 Basic 64-bit, Windows Win8 Dro 64-bit, Windows Win8 Enterprise N 64-bit, Windows	Compatible operating systems	Windows Win8 Basic 32-bit, Windows Win8 Pro 32-bit, Windows Win8 Enterprise 9.2-bit, Windows Win8 Enterprise 9.2-bit, Windows Win8 Enterprise 9.2-bit, Windows Win8 Enterprise 9.2-bit, Windows Win8 Enterprise 9.32-bit, Windows Win8 Enterprise 9.2-bit, Windows Win8 Enterprise 9.32-bit, Windows Win8 Enterprise 9.3	
Control panel 3.0-in intuitive touchscreen control panel with colour graphic display; 3 Buttons (Home, Help, Back) Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz), 220-volt input voltage: 220 to 240 VAC (+/- 10%), 60 Hz (+/- 3 Hz), (Not dual voltage, product varies by part number with # Option code identifier); Power consumption: 365 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Bue, Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Bue, Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Bue, Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Bue, Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (P	Minimum system requirements	PC: Windows: Windows XP (SP3) 32-bit and 64-bit, Windows Win7 (Including Starter Edition 32-bit and 64-bit), Windows Vista Including Starter Edition 32-bit, Windows Vista Including Starter Edition 32-bit, Windows Win8 Pro 64-bit, Windows Win8 Enterprise 32-bit, Windows Win8 Enterprise	
Control panel 3.0-in intuitive touchscreen control panel with colour graphic display; 3 Buttons (Home, Help, Back) Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz), 220-volt input voltage; 220 to 240 VAC (+/- 10%), 60 Hz (+/- 3 Hz), (Not dual voltage, product varies by part number with # Option code identifier); Power consumption: 365 wats (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Blue Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Blue Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Blue Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Blue Angel Sleep), 0.97 watts (Print/Copy), 10.5 watts (Pr	Fonts and typefaces	84 scalable TrueType fonts. Additional Font	Solutions available at hp.com/go/laserjetfonts
Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 60 Hz (+/- 3 Hz); (Not dual voltage, product varies by part number with # Option code identifier); Power consumption: 365 watts (Print/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Blue Angel Sleep), 0.97 watts (HP Auto-Off/Auto-On - Wake on LAN), 0.1 watts (Auto-Off/Manal-On), 0.1 watts (Manal-Off) (Auto-Off/Manal-On), 0.1 watts (Manal-Off) (Auto-Off/Manal-On), 0.1 watts (Manal-Off) (Auto-Off/Manal-Off) (Aut		**	
voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 10 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 10 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 10 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 10 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 10 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 10 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 10 to 127 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz); 220 valts (Hz) value in the proper value val			
Software included Inbox CD (Windows Partition): HP Installer/Uninstaller, HP PCL 6 print driver, DXP (Device Experience), User Guide, HP Send Fax, HP Device Toolbox, HP Fax Print Driver, HP Fax Setup Wizard, HP PM Improvement Study, HP Scan, HP TWAIN & WIA Scan Drivers, Scan to e-mail setup Wizard, Scan to Folder Setup Wizard, HP Update, Product Registration Assist, HP Web Services Assist, HP Connection (a. 8.5 SP1 (only installed for older Windows operating systems that lack); Inbox CD (Mad Partition): Web Redirects users to h_n.com_, or OS App Source for HP Laserslet Software) Acoustic Acoustic power emissions: 6.4 B(A) (printing at 18 ppm); Acoustic power emissions (ready): Inaudible; Acoustic pressure emissions bystander (acdy): Inaudible; Acoustic pressure emissions bystander (acdy): Inaudible; Acoustic pressure emissions bystander (acdy): Inaudible; Derating temperature range: 15 to 30° C (59 to 86° F); Recommended operating temperature: 15 to 30° C (59 to 86° F); Recommended operating humidity range: 10 to 80% RH. Security management Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SMMPv1 & SNMPv2 community password change; HP ePrint: HT certificate validation, HTTP Basic Access Authentication; LDAP authentication and authorization; Firewall and ACL; SNMPv3 Safety approvals and requirements EN 60950-1:2006 *A11:2009 *A11:2011; EC 60950-1:2005 *A11:2009; EN 60825-1:2007 (TeC 60825-1:2007 (Tass 1 Laser Product); EN 62479:2010; CAN/CSA Ca 60950-1-07 2nd Ed.March 27, 2007 Compliance of IEC 60950-1:31 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007 TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, Autol) P.	Power	voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz), 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz) (Not dual voltage, product varies by part number with # Option code identifier); Power consumption: \$0.5 watts (Product), 10.5 watts (Ready), 2.7 watts (Sleep), 1.73 watts (Blue Angel Sleep), 0.97 watts (HP Auto-Off/Auto-On - Wake on LAN), 0.1 watts	voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz) (Not dual voltage, product varies by part number with # Option code identifier); Power consumption: 456 watts (Pirnt/Copy), 10.5 watts (Ready), 2.7 watts (Sleep), 2.69 watts (Blue Angel Sleep), 0.97 watts (HP Auto-Off/Auto-On - Wake on LAN), 0.1 watts
Acoustic pressure emissions bystander (ready): Inaudible Environmental ranges Operating temperature range: 15 to 30° C (59 to 86° F); Recommended operating temperature: 15 to 30° C (59 to 86° F); Non-operating humidity range: 0 to 95% RH; Operating humidity range: 10 to 80% RH Security management Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 & SNMPv2 community password change; HP ePrint: HTI certificate validation, HTTP Basic Access Authentication, SASL authentication; LDAP authentication; Frewall and ALL; SNMPv1 & SAMPv1 & SNMPv1 & S	Software included	Improvement Study, HP Scan, HP TWAIN & WIA Scan Drivers, Scan to e-mail setup Wizard, Scan to Fol	der Setup Wizard, HP Update, Product Registration Assist, HP Web Services Assist (HP Connected), .NE
Environmental ranges Operating temperature range: 15 to 30° C (59 to 86° F); Recommended operating temperature: 15 to 30° C (59 to 86° F); Non-operating humidity range: 0 to 95% RH; Operating humidity 10 to 80% RH; Recommended operating humidity range: 10 to 80% RH; Security management Embedded Web Server: password-protection, secure browning uis SSL/TLS; Network: enable/disable network ports and features, SNMPv1 & SNMPv1 & SNMPv2 community password change; HP ePrint: HT1 certificate validation, HTTP Basic Access Authentication, SASL authentication; LDAP authentication and authorization; Firewall and ACL; SNMPv3 Safety approvals and requirements EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011; IEC 60950-1:2005 +A1:2009; EN 60825-1:2007 / IEC 60825-1:2007 (Class 1 Laser Product); EN 62479:2010 / IEC 62479:2010; CAN/CSA Cide (Compliance of IEC 60950-1:2006 +A11:2009) and 1040.11 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007 Supported network protocols TCP/IR: IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing; Discovery; EIP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutolP, Name Printing) and the printing of the Compliance of IEC 60950-1 and Indiance of IEC 60950-1 and IEC 609	Acoustic		
Security management Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 & SNMPv1 & SNMPv2 community password change; HP ePrint: HTT certificate validation, HTTP Basic Access Authentication, SASL authentication; LDAP authentication and authorization; Firewall and ACL; SNMPv2 Safety approvals and requirements EN 60950-1:2006 +411:2009 +112:2011; EC 60950-1:2005 +13:2009; EN 60825-1:2007 (Tass 1 Laser Product); EN 62479:2010 (Tass 1 Laser Produ	Environmental ranges	Operating temperature range: 15 to 30° C (59 to 86° F); Recommended operating temperature: 15 to 30° C (59 to 86° F); Non-operating humidity range: 0 to 95% RH; Operating humidity range:	
Safety approvals and requirements EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011; IEC 60950-1:2005 +A1:2009; EN 60825-1:2007 / IEC 60825-1:2007 (Class 1 Laser Product); EN 62479:2010 / IEC 62479:2010; CAN/CSA Cidentific Compliance of IEC 60950-1 standard considers all country deviations according to the most recent IECEE CB Bulletin; Compliance with Laser safety standards and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007 Supported network protocols TCP/IR IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing; Discovery; EIP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, Autol) P.	Security management	Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 & SNMPv2 community password change; HP ePrint: HTTPS with	
Supported network protocols TCP/IR, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Printing; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Printing; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Printing; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Discovery: IP Config: IPv4 (BootP, DHCP, Autol), Neb Services Discovery: IPv4 (BootP, DHCP, Autol), Neb Services Discov	Safety approvals and requirements	EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011; IEC 60950-1:2005 +A1:2009; EN 60825-1:2007 / IEC 60825-1:2007 (Class 1 Laser Product); EN 62479:2010 / IEC 62479:2010; CAN/CSA C22.2 No 60950-1-07 2nd Ed.March 27, 2007 Compliance of IEC 60950-1 standard considers all country deviations according to the most recent IECEE CB Bulletin; Compliance with Laser safety standards 21 CFR	
IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); management: SNMPv1, SNMPv2, SNMPv3, HTTP	Supported network protocols	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services I	Printing; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual)

¹ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see https://pc.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. ² Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software. ³ First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <a href="https://pc.ncb/pc.n

To learn more, visit hp.com

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Microsoft and Windows are registered trademarks of Microsoft Corporation. AirPrint and the AirPrint logo are trademarks of Apple Inc., registered in the U.S. and other countries. Linux is a U.S. registered trademark of Linus Torvalds. Red Hat Enterprise Linux Certified is a registered trademark of Red Hat Inc. in the United States and other countries.

