B730 Specifications





Business printing performance you can rely on

The B730 A4 mono printer brings very fast, reliable and affordable printing to the busy large-sized workgroup requiring larger volume capability. The B730 combines advanced security, management and performance with robust and durable technology offering speeds of 50 pages per minute (ppm) for improved office efficiency.

The B730 improves large workgroup productivity through fast print speeds, effective network management and reduced user intervention. Combine this with a low total cost of ownership, simple network integration and an intuitive control panel with a 5-line LCD back-lit display, you get a printer that offers complete versatility in any working environment.

Fast and affordable printing

The B730 prints a quick 50ppm and not only has a class-leading combination of high standard RAM memory (128MB) and fast processing power, but also offers two input trays as standard (700 sheets) for flexible media handling, which can be expanded up to 1,800 sheets. The optional Offset Catch Tray can be added to ease job separation. The B730 is also fully compatible with PCL/PostScript and its 1,200 x 1,200dpi resolution ensures pin-sharp output every time – a must for all customer facing documents and output.

Low total cost of ownership

Bringing affordable printing closer to the workgroup, the B730 combines low hardware costs with a high yield toner cartridge up to 25,000 pages reducing both your capital and consumables costs. The single consumable is changed in seconds ensuring the printer is always 'ready' for business critical processes. The B730 delivers a reduced total cost of ownership and will continue to provide value for money and reliable printing now and in the future.

Easy management and simple security

Printing securely and protecting sensitive information has never been easier. The B730 allows you to print securely using a pin number, which can be entered through a numeric keypad to release the job. This simple to use system ensures that only people selected by you, can access your sensitive documents for print. The PrintSuperVision network management software enables control and visibility over the network, to maintain the printers in optimal condition and ready to print always. For even faster performance a 1Gigabit network card can be added as an option. The integrated USB port allows PDF files to be printed direct from a USB stick for added flexibility.

Built to last

The B730 is designed to perform in the most demanding environments. The robust design and innovative technology not only delivers outstanding reliability but also offers you consistently high quality print over and over again.

Saving money and energy

Built to meet Energy Star and Blue Angel certification, the B730 is kind to the environment, providing energy savings, reducing costs and CO₂ emissions. The duplex model will also reduce paper usage significantly.

| A4 | ~ |
|-------------------------|---|
| Range of media handling | ~ |
| Mono | ~ |
| Print | ~ |
| 1-30 users | ~ |

Variants available: B730n networked B730dn duplex, networked



B730 - Mono Printers

| Statutal RAM: 12/000; MaXINUT RAM: 04/006 Memory Flash Memory: 40/08 on board for storage of fonts, form and macros Optional Compact Flash Memory: up to 1024MB JSB Port for Environment Server for int. Includes otocols sup- ICC/BOOTP, Dynamic DNS, V/3, Ethertalk, PSec, 802.1x Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Dynamic DNS, V/3, Ethertalk, PSec, 802.1x Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% Dynamic DNS, V/3, Ethertalk, PSec, 802.1x Dimensions (HxWXD) B730n: 404 x 422 x 4572mm Dynamic DNS, V/3, Ethertalk, PSec, 802.1x Dimensions (HXWXD) B730n: 404 x 422 x 456mm; B730dn: 404 x 422 x 572mm Vist & 64-bit) / ver 2003 (32-bit S \$10.2 - 10.6 Duty cycle Maximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month S 11.2 - 10.6 Warranty 1 year Pan-European warranty PDF Print Status Monitor ² Offset catch tray 01279601; B730dn: 01278701 Accessories (ORDER NUMBERS) Status 09004629 Status 09004630 Gigabit Ethernet Card 99004584 09004634 01279001 fism Length Black print cartridge | A4 Print speed | 50ppm | Resolution | 600x600dpi, 1200 x 1200dpi | |
|--|-------------------------------|--|--|---|--|
| Standard KAM: 1240MB Memory Flash Memory: 40MB on board for storage of fonts, form and macros Optional Compact Flash Memory: up to 1024MB Description Environment 15B Port for Environment 1FX), Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% server for nnt. Includes otocols sup- ICP/BOOTP, Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% Power save: 10.3W Operating: 66dB(A) or less; Standby: 169W; Power Save: 10.3W Dynamic DNS, (V3, Ethertalk, PSec, 802.1x Dimensions (HxWXD) B730n: 21.1kg; B730dn: 23.2kg Weight* B730n: 21.1kg; B730dn: 23.2kg Maximum: 200.000 pages/month; Recommended: 5,000 - 20,000 pages/month V3 12.2 - 10.6 Warranty 1 year Pan-European warranty PDF Print Status Monitor ² Offset catch tray 01279601 Gigabit Ethernet Card 09004584 09004584 per scom-9, K6, B5, Letter, stom size: With mom, 9, Com-10, gal 13 & 14, 15mm Length Gompact Flash Memory 1GB*: 09004630 Gaste print cartridge* (15,000 pages) 012 | Time to first print | 8 Seconds | GENERAL FEATURES | | |
| Memory macros macros 0ptional Compact Flash Memory: up to 1024MB 0ptional Compact Flash Memory: up to 1024MB SB Port for 1FX), Power supply 2.00, 15B Port for Final Compact Flash Memory: up to 1024MB Operating temperature/ humidity: 5°C to 35°C/ 15% to 85% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing server for int. Includes otocols sup- ICP/BOOTP, Dower sove: 10.3W DOParating: 66dB(A) or less; Standby: 30dB(A) or less; Power save: 10.3W Power sove: 10.3W V3, Ethertalk, Power sove: 10.3W PSec, 802.1x Weight B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm PSec, 802.1x Weight B730n: 21.1kg; B730dn: 23.2kg Maximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month 1 Ver 2003 (32-bit Duty cycle Maximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month S 10.2 - 10.6 Warranty 1 year Pan-European warranty PF Print Status Monitor ² Offset catch tray S of 80gsm 3rd/ 4th tray 01279601 Gigabit Ethernet Card | Warm up time | Up to 38 seconds from power on & up to 25 seconds from power save | | Standard RAM: 128MB; Maximum RAM: 640MB | |
| 2.0, JSB Port for Environment Operating temperature/ humidity: 5°C to 35°C/ 15% to 85% RF non-condensing 1FX), Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing server for mt. Includes otocols sup- ICP/BOOTP, Dynamic DNS, /v3, Ethertalk, IPSec, 802.1x Power consumption Typical: 904W; Max: 1200W; Standby: 169W; Power Save: 10.3W Dynamic DNS, /v3, Ethertalk, IPSec, 802.1x Dimensions (HxWxD) B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm VBS 10.2 - 10.6 Dimensions (HxWxD) B730n: 014 x 422 x 465mm; B730dn: 404 x 422 x 572mm VS 10.2 - 10.6 Weight* B730n: 01278601; B730dn: 01278701 Ver 2003 (32-bit SX 10.2 - 10.6 Warranty 1 year Pan-European warranty PDF Print , Status Monitor ² Product order numbers B730n: 01278601; B730dn: 01278701 Accessories (ORDER NUMBERS) Offset catch tray 01279601 Gifset catch tray 01279601 108 ⁵ : 09004634 u-9, Com-10, ga113 & 14, 15mm Length ConsumABLES (ORDER NUMBERS) 01279001 Black print cartridge* (15,000 pages) 01279001 01279001 Hard Disk Drive (25,000 pages) 01279201 01279201 | Processor speed | | | | |
| Accessor Browneet bisb Environment nr.condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing Operating: 66dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Power Save: 10.3W B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm PSec, 802.1x Weight B730n: 20.2000 pages/month; Recommended: 5,000 pages 1 year Pan-European warranty PDF Print Product order numbers B730n: 01278601; B730dn: 01278701 Acccessories (ORDER Nu | NTERFACE AND SOFTWARE | | | Optional Compact Flash Memory: up to 1024MB | |
| Storage temperature/humidity: 0°C to 35°C, 15% to 80% RH non-condensing 1 FX), Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% server for nt. Includes Power consumption 00cols sup- ICP/BOOTP, Dynamic DNS, V3, Ethertalk, PSec, 802.1x Power sove: 10.3W 00perating: 66dB(A) or less; standby: 30dB(A) or less; Power save: 10.3W 01mensions (HxWxD) B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm PSec, 802.1x Weight* bit & 64-bit) / V97 2003 (32-bit Duty cycle Maximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month; Recommended: 5,000 - 20,000 pages/month 1 year Pan-European warranty PP Print , Status Monitor ² Product order numbers 8 of 80gsm Duplex 01279401 (Standard on B730dn: 01278701 Accessories (ORDER NUMBERS) 09004584 01279501 0ffset catch tray 01279601 01279601 icio, Executive, , Custom size: Pes: Com-9, 6 Status Opo04629 4068*: 09004630 64, B5, Letter, stom size: Width m-9, Com-10, gat1 3 & 14, 15mm Length Compact Flash Memory 1GB*: 09004630 if sigabit Ethernet Card (15,000 pages) 01279001 01279001 igsm Black print cartridge* (25,000 pages) 01279001 | Connectivity | IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0, 10/100BaseTX Ethernet, RS-232C Serial, Host USB Port for | - Environment | | |
| 172), Power supply 230VAC +/- 10%, 50 or 60Hz +/- 2% server for nt. Includes Power consumption Typical: 904W; Max: 1200W; Standby: 169W; Power Save: 10.3W 00perating: 66dB(A) or less; Standby: 30dB(A) or less; Power save: Background level (including all available options) V73, Ethertalk, PSec, 802.1x Dimensions (HxWxD) B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm •bit & 64-bit) / Ver 2003 (32-bit Vs 2003 (32-bit S x 10.2 - 10.6 , PDF Print , Status Monitor ² Duty cycle Maximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month s of 80gsm Product order numbers B730n: 01278601; B730dn: 01278701 Accessories (ORDER NUMBERS) Offset catch tray 01279401 (Standard on B730dn) s of 80gsm 3rd/ 4th tray 01279501 Offset catch tray 01279601 1B ³ : 09004629 (6, B5, Letter, stom size: Width m-9, Com-10, B13 & 14, 15mm Length ConsumABLES (ORDER NUMBERS) Black print cartridge* (15,000 pages) Black print cartridge* (25,000 pages) 01279001 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages 01279201 | | direct printing of PDF | | | |
| Power consumption Power Save: 10.3W Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power Save: 10.3W Weight* B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm Product order numbers B730n: 01278001: 23.2kg Maximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month S of 80gsm Duplex 01279401 (Standard on B730dn: 01278701 Accessories (ORDER NUMBERS) Offset catch tray 01279501 Offset catch tray 01279601 01279601 icio, Executive, (Listom size: Width m-9, Com-10, gal 13 & 14, 15mm Length Gompact Flash Memory | Printer languages | PCL6, PCL5e, Adobe® PostScript 3, SIDM (Epson FX), Direct PDF printing | | | |
| ICP/BOOTP, Dynamic DNS, V/3, Ethertalk, IPSec, 802.1x Noise level Operating: 66dB(A) or less; Standby: 30dB(A) or less; Power save: Background level (including all available options) IPSec, 802.1x Dimensions (HxWxD) B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm IPSec, 802.1x Weight* B730n: 21.1kg; B730dn: 23.2kg *bit & 64-bit) / ver 2003 (32-bit SX 10.2 - 10.6 Duty cycle Maximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month Y PDF Print , Status Monitor ² Product order numbers B730n: 01278601; B730dn: 01278701 Accessories (ORDER NUMBERS) 01279401 (Standard on B730dn) icio, Executive, , Custom size: pes: Com-9, 46, B5, Letter, stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length Offset catch tray Compact Flash Memory 1GB ⁵ : 09004629 Memory 512MB: 09004634 01279001 Black print cartridge* (15,000 pages) 01279001 Black print cartridge* (25,000 pages) 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages | Network & protocols | 10/100Base TX Ethernet card with internal web server for printer and network card set-up and management. Includes SMTP mail client for alerts. All major network protocols sup- ported: TCP/IP: IPv4, IPv6, ICMP, ARP, RARP, DHCP/BOOTP, "Port 9100", LPR/LPD, Apple Bonjour (mDNS), Dynamic DNS, DNS/WINS, HTTP, SMTP, POP3, FTP, SNMPv1/v2/v3, Ethertalk, Netware IPX/SPX, Network Security Protocols: IPSec, 802.1x Wired Authentication: EAP-MD5, PEAP, EAP-TLS | Power consumption | | |
| J/3, Ethertalk, IPSec, 802.1xDimensions (HxWxD)B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mmIPSec, 802.1xWeight*B730n: 21.1kg; B730dn: 23.2kg*-bit & 64-bit) / ver 2003 (32-bitDuty cycleMaximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month*-bit & 64-bit) / ver 2003 (32-bitDuty cycleMaximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month*-bit & 64-bit) / ver 2003 (32-bitDuty cycleMaximum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month*-bit & 64-bit) / ver 2003 (32-bitProduct order numbersB730n: 01278601; B730dn: 01278701*-bit & 64-bit / ver 2003 (32-bitProduct order numbersB730n: 01278601; B730dn: 01278701*-bit & 64-bit / ver 2003 (32-bitOtffset catch tray01279401 (Standard on B730dn)*-s of 80gsmDuplex01279401 (Standard on B730dn)*-s of 80gsmOffset catch tray01279601icio, Executive, p. Curb size: pes: Com-9, (A, Egs bit Ethernet Card09004584*-s of 80gsmS12MB: 09004629*-s of 80gsmConsumABLES (ORDER NUMBERS)*-s of 80gsmBlack print cartridge* (15,000 pages)*-s of 80gsmBlack print cartridge* (25,000 pages)*-s of 84 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 p | | | Noise level | | |
| Weight*B730n: 21.1kg; B730dn: 23.2kgWeight*B730n: 21.1kg; B730dn: 23.2kgWainum: 200,000 pages/month; Recommended: 5,000 - 20,000 pages/month; Recommended: 5,000 - 20,000 pages/monthS X 10.2 - 10.6WarrantyPDF Print , Status Monitor21 year Pan-European warrantyPoduct order numbersB730n: 01278601; B730dn: 01278701Accessories (ORDER NUMBERS)s of 80gsmDuplex01279401 (Standard on B730dn)s of 80gsm01279401 (Standard on B730dn)(cist, Executive, , Custom size: pes: Com-9, 46, B5, Letter, stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length1Gigabit Ethernet Card 40GB*: 09004630ConsumABLES (ORDER NUMBERS)Black print cartridge* (15,000 pages)01279001Black print cartridge* (25,000 pages)01279201*Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 p | | | Dimensions (HxWxD) | B730n: 404 x 422 x 465mm; B730dn: 404 x 422 x 572mm | |
| Duty Cycle Recommended: 5,000 - 20,000 pages/month Ver 2003 (32-bit (SX 10.2 - 10.6) , PDF Print , Status Monitor ² 1 year Pan-European warranty Product order numbers B730n: 01278601; B730dn: 01278701 Accessories (ORDER NUMBERS) Accessories (ORDER NUMBERS) s of 80gsm Duplex 01279401 (Standard on B730dn) s of 80gsm 3rd / 4th tray 01279501 Offset catch tray 01279601 icio, Executive, , Custom size: pes: Com-9, Stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length Memory 512MB: 09004629 ConsumABLES (ORDER NUMBERS) 406B ⁵ : 09004630 01279001 Black print cartridge* (15,000 pages) 01279001 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages 01279201 | | | Weight ⁴ | B730n: 21.1kg; B730dn: 23.2kg | |
| PDF Print , Status Monitor ² Warranty Pedar Function Conference on the confe | OS Compatibility ¹ | & 64-bit) / Server 2008 (32-bit & 64-bit); Mac OS X 10.2 - 10.6 | Duty cycle | | |
| Status Monitor ² Product order numbers B730n: 01278601; B730dn: 01278701 s of 80gsm 01279401 (Standard on B730dn) s of 80gsm 01279401 (Standard on B730dn) s of 80gsm 01279501 Offset catch tray 01279601 icio, Executive,, (Custom size: pes: Com-9, 46, B5, Letter, stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length 1 Gigabit Ethernet Card 09004584 Compact Flash Memory 12B ⁵ : 09004629 Memory 512MB: 09004634 Memory 16B ⁵ : 09004630 ConsumAbles (ORDER NUMBERS) Black print cartridge* (15,000 pages) 01279001 Black print cartridge* (25,000 pages) 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 p. | | | Warranty | 1 year Pan-European warranty | |
| s of 80gsm Duplex 01279401 (Standard on B730dn) s of 80gsm 3rd/4th tray 01279501 icio, Executive, 01279601 , Custom size: 1 Gigabit Ethernet Card 09004584 pes: Com-9, Memory 512MB: 09004629 X6, B5, Letter, Compact Flash Memory 1GB ⁵ : 09004634 m-9, Com-10, Hard Disk Drive 40GB ⁵ : 09004630 Gassm ConsumAbles (ORDER NUMBERS) 01279001 Black print cartridge* 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages) 01279201 | Utility suite ¹ | Template Manager ² , PrintSuperVision, OKI LPR ² , PDF Print Direct, Secure Print, Storage Device Manager ²⁸³ , Status Monitor ² | | | |
| s of 80gsm Duplex 01279401 (Standard on B730dn) s of 80gsm 3rd/4th tray 01279501 icio, Executive, 0ffset catch tray 01279601 icio, Executive, 1 Gigabit Ethernet Card 09004584 yes: Com-9, Memory 512MB: 09004629 X6, B5, Letter, Compact Flash Memory 1GB ⁵ : 09004634 m-9, Com-10, Hard Disk Drive 40GB ⁵ : 09004630 gal 13 & 14, ISmm Length ConsumAbles (ORDER NUMBERS) Black print cartridge* 01279001 igsm (15,000 pages) 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages 01279201 | Paper Handling | | Accessories (Order Numb | HERS) | |
| s of 80gsm 3rd / 4th tray 01279501 icio, Executive, 01279601 , Custom size: 1 Gigabit Ethernet Card 09004584 pes: Com-9, Memory 512MB: 09004629 x6, B5, Letter, Compact Flash Memory 1GB ⁵ : 09004634 m-9, Com-10, Hard Disk Drive 40GB ⁵ : 09004630 gal 13 & 14, ISmm Length CONSUMABLES (ORDER NUMBERS) Black print cartridge* 01279001 gsm (15,000 pages) 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages 01279201 | Paper capacity | Tray 1: 150 sheets of 80gsm; Tray 2: 550 sheets of 80gsm | | | |
| icio, Executive, , Custom size: pes: Com-9, 6, B5, Letter, stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length ConsumABLES (ORDER NUMBERS) Black print cartridge* heets of 80gsm *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 p | Paper capacity optional tray | Tray 3: 550 sheets of 80gsm; Tray 4: 550 sheets of 80gsm | | , , , | |
| 1 Ggabit Ethernet Card 05004384 pes: Com-9, 6, B5, Letter, stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length Memory 512MB: 09004629 Compact Flash Memory 1GB ⁵ : 09004634 Black print cartridge* (15,000 pages) 01279001 Black print cartridge* (25,000 pages) 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages | Maximum paper capacity | 1,800 sheets of 80gsm | Offset catch tray | 01279601 | |
| Desc Com-9, 46, B5, Letter, stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length Memory 512MB: 09004629 Compact Flash Memory 1GB ⁵ : 09004634 Compact Flash Memory 1GB ⁵ : 09004634 Black Drive 40GB ³ : 09004630 Black print cartridge* (15,000 pages) 01279001 Black print cartridge* (25,000 pages) Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 p. | Paper sizes | Tray 1: A4, A5, A6, B5, Letter, Legal 13 & 14, Oficio, Executive, Statement, Banner size: 210 x 900, 210 x 1200, Custom size: Width 76-215mm Length 127-1219mm, Envelopes: Com-9, Com-10, DL, C5, Monarch; Tray 2/3/4: A4, A5, A6, B5, Letter, Legal 13 & 14, Oficio, Executive, Statement, Custom size: Width 98-215mm Length 148-355mm, Envelopes: Com-9, Com-10, DL, Monarch; Duplex: A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 88-215mm Length 139-355mm | 1 Gigabit Ethernet Card | 09004584 | |
| Stom size: Width m-9, Com-10, gal 13 & 14, 15mm Length Compact Flash Memory 10B*: 09004634 Hard Disk Drive 40GB ⁵ : 09004630 Black print cartridge* (15,000 pages) 01279001 Black print cartridge* (25,000 pages) 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages) | | | Memory | 512MB: 09004629 | |
| m-9, Com-10, gal 13 & 14, 15mm Length CONSUMABLES (ORDER NUMBERS) Black print cartridge* heets of 80gsm *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pp | | | Compact Flash Memory | 1GB⁵: 09004634 | |
| Black print cartridge* (15,000 pages) 01279001 Black print cartridge* (25,000 pages) 01279201 *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages | | | Hard Disk Drive | 40GB ⁵ : 09004630 | |
| Image: system Image: system Image: system heets of 80gsm *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages | | | Consumables (Order Numbers) | | |
| Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Control of the second system Image: Contro of the second system Image: Control of the second | Paper weight | | | 01279001 | |
| heets of 80gsm *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 pages | Duplex | | | | |
| *Number of A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,000 p | Paper output | Face down: 500 sheets of 80gsm; Face up: 70 sheets of 80gsm | | | |
| yield compliant with ISU/IEC 19752 | Optional output tray | | *Number of A4 pages yield comp yield compliant with ISO/IEC 19 | | |
| yield compliant with ISO/IEC 19752 | Duplex Paper output | Tray 1/2/3/4: 64 to 216gsm; Duplex: 64 to 216gsm Standard: B730dn; Optional: B730n Face down: 500 sheets of 80gsm; Face up: 70 sheets of 80gsm | (15,000 pages) Black print cartridge* (25,000 pages) *Number of A4 pages yield comp | 01279201 Dliant with ISO/IEC 19752. Printer shipped | |

 Printer fonts
 PostScript 3: Adobe Standard 136

 Dot matrix fonts
 Epson FX

 Barcode
 11 types of one dimension with 28 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET

¹Check local OKI Printing Solutions website for latest driver releases and OS compatibility; ²Windows only; ³Hard Disk Drive required; ⁴Including all consumables; ⁵Minimum specification, subject to change

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI SYSTEMS (POLAND) LTD.

Domaniewska Str. 42 02-672 Warsaw, Poland T +48(0) 22 44 86 500 F +48(0) 22 44 86 501 www.oki.pl



