

The Dell 1135n multifunction laser printer



Highly affordable 4-in-1 multifunction monochrome laser printer offers superb value for small offices and workgroups

Designed for small businesses and small and home offices, the easy to use, reliable and superbly affordable Dell[™] 1135n multifunction monochrome laser printer offers convenient print, scan, copy and fax capabilities in one compact device.

The Dell 1135n prints up to 22 pages per minute with a maximum monthly duty cycle of up to 12 000 pages. It comes standard with a 250 sheet paper drawer and 128 MB RAM, delivering high efficiency and reliability. Its enhanced 2-inch LCD user interface and numeric keypad make it easy to use and its enhanced 4800 x 4800 dpi scanning capabilities set it apart from the competition.

Enjoy speed, reliability and exceptional immediate and long-term value in a compact and ready to use multifunction monochrome laser printer with the Dell 1135n.



Product benefits

Low total cost of printing

Get exceptional value with the affordably priced Dell 1135n multifunction monochrome laser printer. Then save money over time — Dell high-capacity mono toner cartridges deliver a low cost per page. Factoring in its excellent reliability and outstanding support, the Dell 1135n printer is the right choice for small businesses looking for ways to maximize their IT budget.

Impressive speed, quality, and productivity with enhanced features

Get performance-packed functionality and ease of use in this 4-inone model. Instead of depending on multiple machines, enjoy high quality printing, scanning, copying and faxing in one convenient and affordable system featuring an enhanced 2-inch LCD user interface and enhanced resolution 4800 x 4800 dpi scanning capabilities. No need to wait on print jobs with the remarkable speed of the Dell 1135n, which prints 22 A4 pages per minute¹ (ppm) (actual print speed will vary with use).

Enjoy sharp, professional quality prints and experience outstanding productivity and reliability with the Dell 1135n, which handles a high 12 000 pages maximum monthly duty cycle. The Dell 1135n requires minimal maintenance and user attention and offers an optional Dell 2 500 page² high-capacity toner cartridge and 250 sheet paper input drawer standard.

Solid warranty and exceptional service

Should your printer need service, Dell's standard 1 Year Next Business Day Service after Remote Diagnosis³ can help get your Dell 1135n up and running again promptly. Let Dell set up and install your printer with Dell's optional installation services. Focus on your business while we take care of your printers.

Environmentally conscious design-reduce, recycle, renew

Dell's end-of-use programmes include a commitment to recycling printers and toner cartridges. Help protect your bottom line while helping to protect the planet.

According to the US Environmental Protection Agency, Energy Star qualified products are up to 25% more power efficient on average than conventional models.⁴ The Dell 1135n has been designed to help reduce the use of materials and hazardous materials. Dell printer users can return toner cartridges to Dell for recycling at no additional cost (applies to major western European countries only). Dell also helps customers dispose of old printers and other computer equipment in an environmentally conscious manner.

Order supplies online or through selected reseller partners



Dell 1135n side view



Dell 1135n control panel



Dell 1135n back panel

Dell 1135n toner cartridge

Get the most out of your Dell printer with genuine Dell options and supplies

Toner cartridges ²	Dell 1135n black toner cartridge standard capacity (approximately 1 500 pages); or high-capacity (approximately 2 500 pages)	
Memory (RAM)	128 MB RAM	
Connectivity	High-speed USB 2.0, Ethernet 10/100 Base Tx	
Service and support ³	1 year Next Business Day Service after Remote Diagnosis	

Dell 1135n multifunction laser printer



Product description

Reliable and affordable multifunction (print, copy, scan, fax) monochrome laser printer

rioduct description	Reliable and anordable multifunction (print, copy, sear, rax) monochrome laser printer
Printer specifications	
Print speed ¹	Up to 22 A4 pages per minute (ppm)
First page out time	From 'Ready' state: As fast as 9 seconds; From 'Power Saver' mode: As fast as 19 seconds
Print resolutions	600 x 600 dpi (printer default), up to 1200 x 1200 dpi
User interface	Two-line LCD, 16 buttons, and a numeric keypad
Data streams	GDI (Graphics Device Interface)
Processor speed	360 MHz
Memory (RAM)	128 MB SDRAM DDR2 667Mhz
Memory expansion	Not available
Maximum duty cycle	Up to 12 000 pages per month
Typical monthly print volume	300-1 000 pages
Copy specifications	
Copy speed	Up to 22 A4 pages per minute (ppm)
First copy out time	From 'Ready' State as fast as 12 sec (Platen), as fast as 14 sec (ADF) From 'Power Save' mode as fast as 21 sec (Platen)
Copy resolution	Text and text/photo 600 x 600 dpi (ADF and Platen) Photo - up to 1200 x 1200 dpi (Platen), up to 600 x 600 dp (ADF)
Maximum copies	Up to 99
Reduce/enlarge	25% to 400%
Flatbed copy size	A4, A5, A6, US letter, B5, executive, statement, custom (up to 216 mm x 297 mm)
Copy functionality	ID card, N-up, clone, poster
Reduce/enlarge	Original (100%), Auto Fit, A4 to A5 (71%), LGL to LTR (78%), LGL to A4 (83%), A4 to LTR (94%), Exe to LTR (104%), A5 to A4 (141%), 25%, 50%, 150%, 200%, 400%, Custom: 25% to 400% at 1% increments
Scan specifications	
Scanning method	CIS (Contact Image Scanner)
Scan resolution	Optical: 1200 x 1200 dpi (Colour@Platen), 600 x 600 dpi (B/W@Platen) 600 x 600dpi (ADF); enhanced: 4800 x 4800 dpi
Scan depth	Colour: 16 bit; mono: one bit for lineart and halftone, 10 bits for grey scale
Scanning functionality	Via Control Panel: scan to selected applications. Scan to network folder Via SmarThru [™] : Device Discovery, FileFormat, File Saving location, Resolution, Colour, Scan size
Scale file types (Client) Effective scan area	BMP, PDF, TIFF, JPEG 216 x 297 mm
Fax specifications	
Modem speed	Up to 33.6K bps
Fax transmission speed (LTR)	3 seconds/page
Fax job storage	4 MB or up to 320 pages
Fax functionality	Fax broadcasting, delayed fax/scheduled fax, priority fax, fax forwarding, secure fax receive, remote fax receive,
Speed Dial	distinctive ring pattern, ECM, PC fax 200
Fax/phone/TAM interface	Yes (Extension phone and TAM can be connected)
Paper handling Standard input sources	250 sheet via standard drawer and 1 sheet feeder
Additional input sources	Not available
Maximum input capacity	251 sheets (250 sheet standard drawer and 1 sheet feeder)
Duplex unit	Manual duplex
Standard output destination	80 sheet bin
Automatic document feeder	
ADF type	Simplex
ADF input	Up to 40 sheets (based on 80 g/m²)
Media support	Weight: 80 g/m ² ; width: 142 to 216 mm; length: 148 to 356 mm
Supported media types, sizes ar	
Media types supported	Plain, thin, bond, preprinted, recycled, envelope, transparency, label, cardstock, thick, cotton, coloured, archive
250 sheet standard drawer	Media size: A4, A5, US letter, US legal, executive, folio, Oficio, ISO B5, JIS B5
	<i>Weight:</i> 60 - 120 gsm
Multipurpage trou	Media size: A4, A5, A6, US letter, US legal, executive, folio, Oficio, ISO B5, JIS B5, monarch envelope, DL
Multipurpose tray	
Mullipurpose tray	envelope, C5 Envelope, C6 Envelope, No. 10 envelope
Multipurpose tray	envelope, C5 Envelope, C6 Envelope, No. 10 envelope <i>Weight:</i> 60 - 160 gsm Within 4 mm of all edges of the media

Dell 1135n multifunction laser printer



Network Protocol 4, 5 (32/64 bit), Various Linux OS, Macintosh version (OS x or 10.3 - 10.6) Protocol Stacks: TCP/IPv4/IPv6, HTTP, SNMPV1/v2c/v3Network Print Applications: Port 9100, LPD/LPR, Telnet IPPManagement Services & Device Discovery: HTTP, SNMP (V12v3), MBv2 (RFC1213 compliant), BOOTP, DH Auto IP, WINS, DNS, Bonjour, IGMP, mDNS, SLPIPv6 - Ipsec, ICMPv6, Port 9100, LPD, DHCPv6, DNSv6, HTTP, SNMP (V1 v2 v3) Consumables In conjunction with the printer and software, features include toner level reporting, low toner alerts There ranagement In conjunction with the printer and software, features include toner level reporting, low toner alerts Toner cartridge capacity ² The printer ships with a toner cartridge (up to 700 pages) are available for this printer Toner cartridge capacity ² Standard capacity (up to 1 500 pages), or high capacity (up to 2 500 pages) are available for this printer Toner cartridge capacity ² The printer ships with a toner cartridge up to 700 pages). Standard capacity (up to 1 500 pages), or high capacity (up to 2 500 pages) are available for this printer Toner cartridge capacity ² English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian IEC/EN60950-1 (International); IEC60825-1 (Laser); CE Mark (EU); GS Mark (Germany); GOST and Hygienic (Russia); SASO (Saudi Arabia); SABS (South Africa); UL/LL Listed (UL60950-1 US/Canada); PDA/DHHS (21CFR, Chapter 1, Subchapter J, Clasa-1 Laser, US; CCC (China); other safety approvals required by individual countries. EMC certifications EN55022 class B; E		
Pint languages and fonts GDi Microsoft* Windows* fonts Operating systems (OS) support Windows Server® (32/64 bit), Vista (32/64 bit) / Vista (32/64 bit), 2003 Windows* Server® (32/64 bit), 2008 Windows Server® (32/64 bit), Vanous Linux OS, Macintosh version (OS X or 10.5 X or 10.5 X) Network Protocol Protocol Stacks: TCPI/WAIPX6, HTTP, SMMP/1/2/XONSNetwork Print Applications: Port 9100, LPD/LPR, Telnet IPPManagement Services & Device Discovery HTTP, SMMP (V/XX/S), MIB/2 (IRC1213 compliant), BOOTP, DH Auto IP, WINS, DNS, Bonjour, IGMP, mDNS, SLPIPv6 - Ipsec, ICMPv6, Port 9100, LPD, DHCPv6, DNSv6, HTTP, SNMP (V/XVS), MIB/2 (IRC1213 compliant), BOOTP, DH Auto IP, WINS, DNS, Bonjour, IGMP, mDNS, SLPIPv6 - Ipsec, ICMPv6, Port 9100, LPD, DHCPv6, DNSv6, HTTP, SNMP (V/XVS), MIB/2 (IRC1213 compliant), BOOTP, DH Auto IP, WINS, DNS, Bonjour, IGMP, mDNS, SLPIPv6 - Ipsec, ICMPv6, Port 9100, LPD, UPV6, DNSv6, HTTP, SNMP (V/1 V2 v3) Consumables In conjunction with the printer and software, features include toner level reporting, low toner alerts Toner cardridge capacity* The printer ships with a toner cartridge (up to 700 pages) Toner cardridge capacity* Toner cardridge server/Bite serve		
Operating systems (OS) support Microsoft® Windows® - 2000/XP (32/64 bit) / Vista (32/64 bit) / 2003 Windows® Serve® (32/64 bit), 2003 Network Protocol Windows® Terve® (32/64 bit), Vista		
Windows Server® (32/64 bit), Windows Server® 2008 R2. Windows* 7 (32/64 bit), RedHat* Enterprise Linux* (Network Protocol Protocol Stacks: TCP/IPv4/IPv6, HTTP, SNMPv1/v2c/v3Network Print Applications: Port 9100, LPD/LPR, Telnet IPPManagement Services & Device Discovery. HTTP, SNMP (v1v2v3), MIBv2 (RFC1213 compliand), BOOTP, DH Acto IP WINS, DNS, Sonjour, IGMP, mDNS, SLPIPv6 - Ipsec, ICMPv6, Port 9100, LPD, DHCPv6, DNSv6, HTTP, SNMP (v1 v2 v3) The printer ships with a toner catridge (up to 700 pages) Consumables In conjunction with the printer and software, features include toner level reporting, low toner alerts There rangement In conjunction with the printer and software, features include toner level reporting, low toner alerts There ractridge capacity* The printer ships with a toner catridge (up to 700 pages), ore sized as a resoluble using Dell's recycling program, details of which are included with each product Language and regulatory certifications English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian Triver software User documentational: ECE/E06090-1 (International): E06000	5 5	
Network Protocol Protocol Stacks: TCP/IP-4/IPv6, HTTP, SNMP/L/v2c/A3Network Print Applications: Port 9100, LPD/LPR, Tehnet IPPManagement Services & Device Discovery: HTTP, SNMP (v2v23), MI8v2 (RFC1213 compliant), BOOTP, DH Auto IP, WINS, DNS, Bonjour, IGMP, mDNS, SLPIPv6 - Ipsec, ICMPv6, Port 9100, LPD, DHCPv6, DNSv6, HTTP, SNMP (v1 v2 v3) Consumables Toner management Ship-with toner cartridge capacity ² Toner Management State Safety certifications	Operating systems (OS) support	Windows Server® (32/64 bit), Windows Server® 2008 R2, Windows® 7 (32/64 bit), RedHat® Enterprise Linux® WS
Toner management In conjunction with the printer and software, features include toner level reporting, low toner alerts Ship-with toner cartridge capacity ² The printer ships with a toner cartridge (up to 700 pages). Toner cartridge capacity ² Toner cartridge capacity ² Toner cartridges are recyclable using Dell's recycling program, details of which are included with each product Language and regulatory certifications English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian Ware documentation English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian IEC/EN60950-1 (International); IEC60825-1 (Laser): CS Mark (IC): SMark (Germany): GOST and Hygienic (Russia); SASO (Saudi Arbaib); SASD (Saudi Arbaib); SASD (Saudi Arbaib); IEAD/IH42 (21CFR, Chapter 1, Subchapter 3, Class-1, Laser, US); CCC (Chani); other safety approvals required by individual countries EMC certifications EU (EU countries); COST (Russia); SABS (South Africa); UL/cUL Listed (UL60950-1 UJ/Canada); DEV/EH42 (21CFR, Chapter 1, Subchapter 3, Class-1, Laser, US); CCC (Chani); other safety approvals required by individual countries EMC certifications EU WEEE, ROHS ⁶ compliant, Energy Star ⁶ v1.1 qualified ⁴ Printer management Software included Software included Dell Toner Management System ⁶ intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Printer: 115 kg	Network Protocol	Protocol Stacks: TCP/IPv4/IPv6, HTTP, SNMPv1/v2c/v3Network Print Applications: Port 9100, LPD/LPR, Telnet, IPPManagement Services & Device Discovery: HTTP, SNMP (v1v2v3), MIBv2 (RFC1213 compliant), BOOTP, DHCP, Auto IP, WINS, DNS, Bonjour, IGMP, mDNS, SLPIPv6 - Ipsec, ICMPv6, Port 9100, LPD, DHCPv6, DNSv6, HTTP,
Toner management In conjunction with the printer and software, features include toner level reporting, low toner alerts Ship-with toner cartridge capacity ² The printer ships with a toner cartridge (up to 700 pages). Toner cartridge capacity ² Toner cartridge capacity ² Toner cartridges are recyclable using Dell's recycling program, details of which are included with each product Language and regulatory certifications English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian Ware documentation English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian IEC/EN60950-1 (International); IEC60825-1 (Laser): CS Mark (IC): SMark (Germany): GOST and Hygienic (Russia); SASO (Saudi Arbaib); SASD (Saudi Arbaib); SASD (Saudi Arbaib); IEAD/IH42 (21CFR, Chapter 1, Subchapter 3, Class-1, Laser, US); CCC (Chani); other safety approvals required by individual countries EMC certifications EU (EU countries); COST (Russia); SABS (South Africa); UL/cUL Listed (UL60950-1 UJ/Canada); DEV/EH42 (21CFR, Chapter 1, Subchapter 3, Class-1, Laser, US); CCC (Chani); other safety approvals required by individual countries EMC certifications EU WEEE, ROHS ⁶ compliant, Energy Star ⁶ v1.1 qualified ⁴ Printer management Software included Software included Dell Toner Management System ⁶ intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Printer: 115 kg	Consumables	
Ship-with toner cartridge capacity ² The printer ships with a toner cartridge (up to 700 pages) Toner cartridge capacity ² Standard capacity (up to 1500 pages); or high capacity (up to 2500 pages) are available for this printer Toner cartridge and regulatory certifications English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian Printer firmware and printer English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications English, French, Italian, German, Spanish, Dutch, Danish, Vic/UL Listed (UL60950-1 US/Canada); FDA/DH-HS (21CFR, Chapter 1, Subchapter 2, Class 1, Laser, US); CCC (China); other safety approvals required by individual countries EMC certifications EN55022 Class B, EN61000-3-2; EN 61000-3-3; EN55024, FCC CFR Title 47, Part 15 Class B (USA); ICES-003 Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ⁶ compliant, Energy Star ⁶ v1.1 qualified* Printer management Software included Dell Toner Management System ¹⁴ intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions		In conjunction with the printer and software, features include toner level reporting, low toner alerts
Toner recycling Toner cartridges are recyclable using Dell's recycling program, details of which are included with each product Language and regulatory certifications English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian Printer firmware and printer English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian EXC certifications English, SASO (Saudi Arabia); SABS (South Africa); UL/cUL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter 3, Class B; EN61000-3-2; EN 61000-3-3; EN55024; FCC CPR Title 47, Part 15 Class B (USA); ICES-003 (Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoH5 [®] compliant, Energy Star [®] v1.1 qualified ⁴ Physical specifications Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Printer: 416 mm x 415 mm x 319 mm Shipiping carton:	Ship-with toner cartridge capacity ²	
Language and regulatory certifications Printer firmware and printer driver software English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian User documentation English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian IEC/EN60950-1 (International); IEC60825-1 (Laser); CE Mark (EU); CS Mark (Germany); GOST and Hygienic (Russia); SASO (Saudi Arabia); SABS (South Africa); UL/CLL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter 3, Class -1 Laser, US); CCC (China); other safety approvals required by individual countrie EN55022 Class B; EN61000-3-2; EN 6000-3-3; EN55024, FCC CRT Thite 47, Part IS Class B (USA); ICES-003 (Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia), and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ^a compliant, Energy Star [®] v11 qualified ⁴ Printer management Software included Dell Toner Management System [®] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Printer: 115 kg Operating environment Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m Storage (upackaged): air temperature 20°C to 40°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m Storage (upackaged): air temperature 20°C to 40°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m Storage (upackaged): air temperature 20°C to 40°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m Storage (upackag		
Printer firmware and printer English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian driver software English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian EMC certifications English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian EMC certifications ENS5022 (Saudi Arabia); SABS (South Africa); UL/cUL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter 3, Class P, EN61000-3-2; EN 61000-3-5; ENS5024; FCC CFR Title 47, Part 15 Class B (USA); ICES-003 ENVironmental compliance (other) EU WEEE, RoHS ⁶ compliant, Energy Staf [®] v1.1 qualified ⁴ Printer management Software included Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Shipping carton: 540 mm x 530 mm x 420 mm Shipping carton: 14.8 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-les Storag	Toner recycling	Toner cartridges are recyclable using Dell's recycling program, details of which are included with each product.
driver software User documentation User documentation English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian IEC/EN60950-1 (International); IEC60825-1 (Laser); CE Mark (EU); GS Mark (Germany); GOST and Hygienic (Russia); SASO (Saudi Arabia); SABS (South Africa); UL/CUL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter J, Class-1 Laser, US); CCC (China); other safety approvals required by individual countries EMC certifications EN55022 Class B, EN61000-3-2; EN 61000-3-5; EN55024, FCC CFR Title 47, Part 15 Class B (USA); ICES-003 (Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ⁶ compliant, Energy Star® v1.1 qualified ⁴ Printer management Software included Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Weight Dimension: I 4.8 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 10 300 m Acoustics ⁶ <td< td=""><td>Language and regulatory certificat</td><td>tions</td></td<>	Language and regulatory certificat	tions
User documentation English, French, Italian, German, Spanish, Dutch, Danish, Norwegian, Iberian Portuguese, Swedish, Russian Safety certifications IEC/EN60950-1 (International); IEC60825-1 (Laser); CE Mark (IEU); GS Mark (Germany); GOST and Hygienic (Russia); SASO (Saudi Arabia); SABS (South Africa); UL/CUL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter 3, Class -1 Laser, US); CCC (China); other safety approvals required by individual countrie EMC certifications EN55022 Class B; EN61000-3-2; EN 61000-3-3; EN55024; FCC CFR Title 47, Part 15 Class B (USA); ICES-003 (Canada); CE (EU countries); COST (Maxis); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ⁵ compliant, Energy Star [®] v1.1 qualified ⁴ Printer management Software included Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dilmensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Weight Printer: 115 kg Shipping carton: 14.8 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 200 m Norage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Acoustics ⁶		English, French, Italian, German, Spanish, Dutch, Norwegian, Iberian Portuguese, Russian
Safety certifications IEC/EN60950-1 (International); IEC60825-1 (Laser); CE Mark (EU); CS Mark (Germany); GOST and Hygienic (Russia); SASO (Saudi Arabia); SASS (South Africa); UL/cUL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter J, Class-1 Laser, US); CCC (China); other safety approvals required by individual countrie EMS5022 Class B; EN61000-3-2; EN 61000-3-3; EN55024; FCC CFR Title 47, Part 15 Class B (USA); ICES-003 (Canada); CE (EU countries); GOST (Russia); SABS (South Africa); UC/CU (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ⁵ compliant, Energy Star® v1.1 qualified ⁴ Printer management Software included Dell Toner Management System [®] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Shipping carton: 540 mm x 530 mm x 420 mm Weight Printer: 11.5 kg Shipping carton: 14.8 kg Operating: air temperature 0°C to 40°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (packaged): air temperature 0°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Acoustics ⁶ Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dDA; copying less than 50 dBA (platen), 52 dBA (ADF); s		
(Russia); SASO (Saudi Arabia); SABS (South Africa); UL/CUL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter J, Class-1 Laser, US); CCC (China); other safety approvals required by individual countrie ENS5022 Class B; EN61000-3-2; EN 61000-3-3; ENS5024; FCC CFR Title 47, Part 15 Class B (USA); ICES-003 (Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ⁶ compliant, Energy Star [®] v11 qualified ⁴ Printer management Software included Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Dimensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Weight Printer: 11.5 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-lee Storage (uppackaged): air temperature -20°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Acoustics ⁶ Printing less than 50 dBA; copying less than 50 dBA (pl		
Chapter 1, Subchapter J, Class-1 Laser, US); CCC (China); other safety approvals required by individual countrieEMC certificationsEN55022 Class B; EN61000-3-2; EN 61000-3-3; EN55024; FCC CR Title 47, Part 15 Class B (USA); ICES-003 (Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries.Environmental compliance (other)EU WEEE, RoHS* compliant, Energy Star* v1.1 qualified4Printer management Software includedDell Toner Management System** intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software.Physical specifications Dimensions – W x D x HPrinter: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm WeightWeightPrinter: 11.5 kg Shipping carton: 14.8 kgOperating environmentOperating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity	Safety certifications	
EMC certifications EN55022 Class B; EN61000-3-2; EN 61000-3-3; EN55024; FCC CFR Title 47, Part 15 Class B (USA); ICES-003 (Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ⁵ compliant, Energy Star [®] v1.1 qualified ⁴ Printer management EU WEEE, RoHS ⁵ compliant, Energy Star [®] v1.1 qualified ⁴ Physical specifications Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Printer: 11.5 kg Shipping carton: 540 mm x 530 mm x 420 mm Shipping carton: 14.8 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Acoustics ⁶ Voltage Q20 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Power consumption Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		
(Canada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other certifications required by individual countries. Environmental compliance (other) EU WEEE, RoHS ⁶ compliant, Energy Star [®] v1.1 qualified ⁴ Printer management Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Printer: 11.5 kg Shipping carton: 540 mm x 530 mm x 420 mm Weight Printer: 11.5 kg Operating environment Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Acoustics ⁶ Voltage 220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Power consumption Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W	FMC certifications	
Environmental compliance (other) certifications required by individual countries. EU WEEE, RoHS ⁵ compliant, Energy Star [®] v1.1 qualified ⁴ Printer management Software included Dell Toner Management System [®] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Weight Printer: 11.5 kg Operating environment Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature 2°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBA Voltage 220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Power consumption Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		
Environmental compliance (other) EU WEEE, RoHS ⁵ compliant, Energy Star® v1.1 qualified ⁴ Printer management Dell Toner Management System™ intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Dimensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Shipping carton: 540 mm x 530 mm x 420 mm Weight Printer: 11.5 kg Shipping carton: 14.8 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Acoustics ⁶ Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBA Voltage 220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		
Software included Dell Toner Management System™ intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Printer: 416 mm x 415 mm x 319 mm Dimensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Printer: 11.5 kg Operating environment Printer: 11.5 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-lee Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Acoustics ⁶ Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBA Voltage 220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Power consumption Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W	Environmental compliance (other)	
Software included Dell Toner Management System™ intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software. Physical specifications Printer: 416 mm x 415 mm x 319 mm Dimensions – W x D x H Printer: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mm Printer: 11.5 kg Operating environment Printer: 11.5 kg Operating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-lee Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Acoustics ⁶ Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBA Voltage 220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Power consumption Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W	Printer management	
Dimensions - W x D x HPrinter: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mmWeightPrinter: 11.5 kg Shipping carton: 14.8 kgOperating environmentOperating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		Dell Toner Management System [™] intelligent toner monitoring proactively notifies you before you run out of toner. Firmware update utility. SmartThru v4 multifunction productivity software.
Dimensions - W x D x HPrinter: 416 mm x 415 mm x 319 mm Shipping carton: 540 mm x 530 mm x 420 mmWeightPrinter: 11.5 kg Shipping carton: 14.8 kgOperating environmentOperating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal 	Physical specifications	
Shipping carton: 540 mm x 530 mm x 420 mmWeightPrinter: 11.5 kg Shipping carton: 14.8 kgOperating environmentOperating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		Printer: 416 mm x 415 mm x 319 mm
WeightPrinter: 11.5 kg Shipping carton: 14.8 kgOperating environmentOperating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		
Operating environmentOperating: air temperature 10°C to 32°C, Relative Humidity 20 - 80%, maximum altitude 2 500 m above sea-le Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 m Storage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 m Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W	Weight	
Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 10 - 80%, maximum altitude 2 500 mStorage (packaged): air temperature -20°C to 40°C, Relative Humidity 20 - 95%, maximum altitude 10 300 mAcoustics6Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		
Acoustics6Printing less than 50 dBA; copying less than 50 dBA (platen), 52 dBA (ADF); standby mode: sound pressure (LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W	Operating environment	
(LpAm) less than 26 dBAVoltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominalPower consumptionPrinting (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		
Voltage220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominalPower consumptionPrinting (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W	Acoustics⁰	
Power consumption Printing (simplex) 420 W; Standby mode 45 W average; Power Saver mode 10 W; Off 1 W		
	3	220 - 240 Volls (V) at 50/60 ± 5 Nertz (Hz) Norminal Printing (cimpley) 420 W: Standby mode 45 W average: Power Saver mode 10 W: Off 1 W
Literal star vit quantea	i ower consumption	
Typical energy consumption (TEC) ⁷ 1.81 kWh per week	Typical energy consumption $(TFC)^7$	
Power Save options User-definable — 1, 5, 10, 15, 20, 30, 45, 60, 120 minutes (default 1 minute)		
Standard warranty and service	Standard warranty and service	
Standard service 24 x 7 online Technical Support for the life of the product.	÷	24 x 7 online Technical Support for the life of the product.
12 months access to Dell's telephone technical printer support queue.		
Service options ³ 2-5 years Next Business Day On-site Service after Remote Diagnosis	Service options ³	2-5 vears Next Business Day On-site Service after Remote Diagnosis
1-5 years Dell ProSupport™	F	

¹ Print speed quoted refers to A4 Simplex (single-sided) page using default print mode. Actual print speed may vary depending upon system configuration, software application and document complexity. Tested in accordance with ISO/IEC 19752 testing methodology. Yields vary with usage and environmental conditions.

³ Service may be provided by third party. Technician will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. Defective unit must be returned. Replacements may be refurbished.

Print Volume is assumed to be printed at 30 minute intervals across a 10 hour business day (0800–1800), 5 days per week. The printer enters standby mode when the print job is complete, and enters sleep mode after the default period. The printer is assumed to remain in sleep mode at all other times including two weekend days. Energy consumption will be further reduced if the printer is powered down when not in use for long periods. Actual energy consumption will vary according to print volume and usage patterns

©2010 Dell Corporation Limited. Dell, the Dell logo and Dell Toner Management System are registered trademarks or trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Microsoft, Windows and Windows NT are registered trademarks or trademarks or trademarks of Microsoft Corporation. Dell Products, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK. v 1.0 June 2010 – 1135n EN