

DocuPrint P115 w / M115 w / M115 fw A4 Monochrome Printers

Affordability and reliability with wireless connectivity



Clever features designed for reliable, cost-efficient printing

The Fuji Xerox DocuPrint P115 w / M115 w / M115 fw are designed as an affordable entry level print solution, offering high quality personal printing combining reliability with the advantage of wireless connectivity.

Productivity and reliability

- Speed and quality. With a print resolution of up to 2400 x 600 dpi and a printing speed of up to 20 ppm, the DocuPrint P115w / M115 w / M115 fw deliver quality print results fast.
- Print faster. A quick warm up time and first page out of just 10 seconds or less, means the DocuPrint P115 w / M115 w / M115 fw are ready to go when you are.
- All-in-one functionality. Multifunction models allow you to print, copy, scan and fax* in an efficient, low cost device giving you maximum productivity.
- Clever features for reliable operation.
 Fuji Xerox is renowned for reliable printing.
 The DocuPrint P115 w / M115 w / M115 fw are no exception with simple engineering and clever new ideas designed for trouble-free printing.

*Only available on DocuPrint M115 fw

Affordable, efficient printing

- Low cost hardware is only half of the story. Thanks to the separate toner and drum cartridge, you will only ever have to replace one component at a time. This results in maximum use of each component, longer operating times and cost savings.
- Save toner save cost. Toner save mode extends the life of the toner cartridge by varying the density of toner that is printed on a page.
- Use less paper and toner. The built in N-UP print feature gives users the ability to save on paper and toner by printing multiple pages on a single sheet of paper. This also reduces the overall cost of printing.



DocuPrint P115 w Wireless Laser Printer



DocuPrint M115 w 3-in-1 Wireless Multifunction Laser Printer



4-in-1 Wireless Multifunction Laser Printer

Clever features designed to reduce paper jams



Rubber dual paper feed rollers. The specially designed dual roller system improves paper feed by accurately picking up one sheet of paper at a time. The rollers are made from a unique rubber material that prevents dust from sticking to them.



Shorter paper path. A short paper path results in smoother printing and reduces the likelihood of paper jams.

Longer paper guides. Paper feed guides are longer than conventional printers minimising paper skew, which reduces the chance of paper-jams.



Mobile printing made easy

Whether it's an iOS or Android device, the Fuji Xerox Print & Scan Utility puts mobile printing at your fingertips. Print stored photo albums, web pages or shoot and print on the qo from your iOS or Android device.

Fuji Xerox Print & Scan Utility can be easily downloaded from the App Store for iOS and Play Store for Android devices.








Connect with a touch of a button

The DocuPrint P115 w / M115 w / M115 fw feature one-touch Wi-Fi setup (WPS 2.0) making Wi-Fi set up effortless and a breeze to share the printer wirelessly among small workgroups. Simply press the WPS button on the Wi-Fi enabled router, then the WPS button on the printer to establish a Wi-Fi connection.



Clever ID Card Copying*

The easy-to-use ID card copy feature allows you to copy both sides of the card or small size document onto the same side of the paper.



*Available on DocuPrint M115 w / M115 fw

Specifications DocuPrint P115 w / M115 w / M115 fw

Product Name	DocuPrint P115 w	DocuPrint M115 w	DocuPrint M115 fw
Function	A4 monochrome printer	A4 monoci	nrome MFP
Print Function			
Print Speed (A4) Print Resolution	Up to 20 ppm ¹ Up to HQ 1200 technology (2400 x 600 dpi)		
First-page-out Time (A4 SEF) (from ready mode)	Up to HQ 1200 technology (2400 x 600 dpi) 10 seconds or less		
Warm-up Time	18 seconds or less (from sleep mode)		(from sleep mode)
·	23 seconds or less (from Power up)	33 seconds or les	s (from Power up)
Memory		32MB	
Processor		200 MHZ	
PDL Connectivity		Host-based USB2.0 Hi-Speed, Wireless (IEEE 802.11b/g/n)	
Supported Operating System	USB2.0 Hi-Speed, Wiletess (IEEC 2021 10/gH)		
Input Paper Size	A4 SEF, Letter SEF, Folio (8.5" x 13") SEF, Legal SEF, A5 SEF/LEF, B5 LEF, Executive LEF		
Pro Pro Pro	,,	Width: 148 to 215.9 mm, Length: 148 to 355.6 mm	
Media Input Capacity	150 sheets 50 sheets		
Media Output Capacity	SU sheets Plain paper, Recycled paper		
Media Types Input Paper Weight	rium paper, recycled paper 64 to 105 gsm		
Automatic Document Feeder		04 to 103 gsili	10 sheets 64-90 gsm
Recommended monthly print volume (approx.)		250~1800 pages	10 silects 04 70 gsili
Monthly Maximum Duty Cycle	10,000 pages		
Print Features	Toner Save Mode, N-up(2,4,9,16, or 25)8, Poster4(4,9,16,25), Header/Footer4 (time & date and/or user ID), Watermarks4, manual duplex printing4, manual booklet printing4		
Discoursians (MADAII)	W 2 / 0 D 220 II 100	manual booklet printing ⁴	W 20F D 2/2 H 2027
Dimensions (WxDxH) Weight	W 340 x D 238 x H 189 mm 4.6 kg	W 385 x D 343 x H 255 mm ⁷ 7.4 kg	W 385 x D 343 x H 283 mm ⁷ 8.3 kg
Weight Operating Environment Temperature	ч.о ку	Storage: 0° C to 40° C; Operating: 10° C to 32.5° C	о.э ку
Humidity	Ор	erating Environment: 20% to 80%RH (without condensate	ion)
Acoustics: Sound Pressure level	Standby: Inaudible,	Standby:	
	Printing: 51 dB(A) or less	Printing: 52	dB(A) or less
Electrical Power Power consumption	Ready/Standby: 40W, Printing: 380W	220–240 VAC, 50/60 Hz Ready/Standby: 50W, Printing: 390W	Ready/Standby: 50W, Printing: 390W
rowei consumption	Deep sleep: 0.7W;	Deep sleep: 0.9W:	Deep sleep: 1.4W;
	ENERGÝ STAŘ® qualified	ENERGÝ STAŘ® qualified	ENERGÝ STAŘ® qualified
TEC value	0.8 k Wh/w	0.8k Wh/w	0.9 k Wh/w
Wireless Specification			
Wireless LAN		IEEE 802.11b/g/n (Infrastructure mode/Ad-hoc mode)	
	IPv6: NDP_RA_DNS Resolver_mDNS_LLMNR responde	or TPR/LPD Custom Raw Port/Port 9100 TPP FTP Server S	responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, P, Web Services (Print)
Security Protocols Wireless Network Security	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	ver, LPR/LPD, Custom Row Port/Port 9100, IPP, FTP Server, S Client, ICMPv6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)	r, web Selvices (Frint) NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP
Wireless Network Security	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, ICMPv6, Web Services (Print) Wireless : SMTP - AUTH	r, web Selvices (Frint) NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP
Wireless Network Security Wireless Network Setup Support Utility	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, ICMPv6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)	r, web Selvices (Frint) NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP
Wireless Network Security Wireless Network Setup Support Utility Copy Function	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 0 cpm ¹ x 600 dpi
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, ICMPv6, Web Services (Print) Wireless : SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 600 16 seconds or less at 1	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm ¹ x 600 dpi 13°C from ready mode
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm ¹ 10 cpm ¹ 12 food dpi 23 °C from ready mode % increments
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-P5K (TKIP/AES), WPA2-P5K (AES) AOSS™: Yes, WPS: Yes Up to 2 Up to 600 16 seconds or less at . 25 - 400% in Up to	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 0 cpm¹ x 600 dpi 23°C from ready mode % increments o 99
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 0 cpm¹ x 600 dpi 23°C from ready mode % increments o 99
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 600 16 seconds or less at 1 25 - 4000 in 1 Up to 1000 pt 1	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 0 cpm¹ 1x 600 dpi 23°C from ready mode 6 increments 7 99 1 copying (N=2,4)
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} , Yes, WPS: Yes Up to 60 16 seconds or less at . 25 - 400 % in Up t ID Card Copy, N in	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 33°C from ready mode 1% increments 0 99 1 copying (N=2,4) ir CIS
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 2 Up to 600 16 seconds or less at 1 25 - 400 % in Up to 1 ID Card Copy, N ir	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 25 from ready mode 36 increments o 99 1 copying (N=2,4) ur CIS dpi (from Scanner Glass),
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 2 Up to 600 16 seconds or less at 1 25 - 400 % in Up to 1 ID Card Copy, N ir	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 33°C from ready mode 1% increments 0 99 1 copying (N=2,4) ir CIS
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Color Optical: up to 600 x 1200 Enhanced: up to 1	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 22 from ready mode 32 from rements o 99 1 copying (N=2,4) ur CIS dpi (from Scanner Glass), 9,200 x 19,200 dpi ⁶ Optical: up to 600 x 600 dpi (from ADF) bit
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Color Optical: up to 600 x 1200 Enhanced: up to 1	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 0 cpm¹ x 600 dpi x3°C from ready mode % increments o 99 1 copying (N=2,4) Irr CIS dpi (from Scanner Glass), 2,200 x 19,200 dpi° Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Legi
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Color Optical: up to 600 x 1200 Enhanced: up to 1* Max 215.9mm x 300mm	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) ur CIS dpi (from Scanner Glass), 2,200 x 19,200 dpi° Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Leg-Folio
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 2 Up to 600 16 seconds or less at: 25 - 400% in 1 Up t ID Card Copy, N ir Color Optical: up to 600 x 1200 Enhanced: up to 1 Max 215.9mm x 300mm	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi x 600 dpi x 600 dpi x 600 mements 0 99 1 copying (N=2,4) 11 cr CIS dpi (from Scanner Glass), 0,200 x 19,200 dpi ⁶ Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Leger Folio , Image, File ⁹
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) ur CIS dpi (from Scanner Glass), 2,200 x 19,200 dpi® Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege, Folio
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 3° C from ready mode % increments o 99 1 copying (N=2,4) Ir CIS dpi (from Scanner Glass), 0,200 x 19,200 dpi³ Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege Folio Image, File³ 7 TWINIONS & 1: Mac: TWAIN/ICA for OS X v10.7.5.
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 22 from ready mode 32 from rements o 99 1 copying (N=2,4) air CIS dpi (from Scanner Glass), 9,200 x 19,200 dpi² Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Leg Folio I, Image, File³ § 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 1.0.9 x
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 60 Up to 600 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Coloi Optical: up to 600 x 1200 Enhanced: up to 1' — 24 Max 215.9mm x 300mm Scan to Email Windows®: TWAIN, WIA for Windows Vista®/Windows 10.8.x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 33°C from ready mode % increments o 99 1 copying (N=2,4) 11 CIS dpi (from Scanner Glass), 2,000 x 19,200 dpi Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege Folio , Image, File 7 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modern Speed	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS***. Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Color Optical: up to 600 x 1200 Enhanced: up to 1' - 24 Max 215.9mm x 300mm Scan to Emai Windows*: TWAIN, WIA for Windows Vista*/Windows 10.8 x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) sir CIS dpi (from Scanner Glass), 2,200 x 19,200 dpi® Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Legrollion Folio , Image, File® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN 14.4 Kbps
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modem Speed Memory Transmission	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Color Optical: up to 600 x 1200 Enhanced: up to 1' - 24 Max 215.9mm x 300mm Scan to Emai Windows®: TWAIN, WIA for Windows Vista® Windows 10.8 x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) ur CIS dpi (from Scanner Glass), 2,200 x 19,200 dpi² Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege Folio , Image, File² 8 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN 14.4 Kbps Up to 400 pages¹0
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Use Scan Function Colour Depth Cocument Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modem Speed Memory Transmission Out-of-paper Reception	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 600 16 seconds or less at: 25 - 400% in Up to 100 Color Optical: up to 600 x 1200 Enhanced: up to 11 Max 215.9mm x 300mm Scan to Emai Windows®: TWAIN, WIA for Windows Vista®/Windows 10.8 x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 33°C from ready mode % increments o 99 1 copying (N=2,4) ar CIS dpi (from Scanner Glass), 9,200 x19,200 dpi® Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Leg Folio , Image, File® 8 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9.x ITU-T G3 PSTN 14,4 Kbps Up to 400 pages¹⁰ Up to 400 pages¹⁰ Up to 400 pages¹⁰
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modern System Moder	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S. Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS***. Yes, WPS: Yes Up to 600 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Colon Optical: up to 600 x 1200 Enhanced: up to 1' — 24 Max 215.9mm x 300mm Scan to Email Windows*: TWAIN, WIA for Windows Vista*/Windows 10.8 x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) sir CIS dpi (from Scanner Glass), 200 x 19,200 dpi° Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Leg Folio , Image, File³ 8 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN 14.4 Kbps Up to 400 pages¹0 Up to 400 pages¹0 Superfine 8dot/mm x 15,4line/mm
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modem Speed Memory Transmission Out-of-paper Reception Fax Resolution Speed Dials	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 600 16 seconds or less at: 25 - 400% in Up to 100 Color Optical: up to 600 x 1200 Enhanced: up to 11 Max 215.9mm x 300mm Scan to Emai Windows®: TWAIN, WIA for Windows Vista®/Windows 10.8 x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) Ir CIS dpi (ffom Scanner Glass), 2,200 x 19,200 dpi°
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modern Speed Memony Transmission Out-of-paper Reception Fax Resolution Speed Dials Broadcasting	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, 1PP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Coloi Optical: up to 600 x 1200 Enhanced: up to 1' - 24 Max 215.9mm x 300mm Scan to Email Windows®: TWAIN, WIA for Windows Vista®/Windows 10.8.x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 33°C from ready mode 1% increments 0 99 1 copying (N=2,4) 11 CIS dpi (from Scanner Glass), 2,200 x 19,200 dpi² Optical: up to 600 x 600 dpi (from ADF) 12 bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Leg Folio 1, Image, File² 7 7Windows² 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x 1TU-T G3 PSTN 14.4 Kbps Up to 400 pages¹² Up to 400 pages¹² Superfine 8dot/mm x 15.4line/mm Up to 99 locations Up to 119 locations, Manual: 20 locations
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Memory Transmission Out-of-paper Reception Fox Resolution Speed Dials Broadcasting Fox Features	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 600 16 seconds or less at 1 25 - 400 % in Up to 100 Optical: up to 600 x 1200 Enhanced: up to 11 - 24 Max 215.9mm x 300mm Scan to Emai Windows®: TWAIN, WIA for Windows Vista®/Windows 10.8.x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTF 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) Ir CIS dpi (ffom Scanner Glass), 2,200 x 19,200 dpi®
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modem Speed Memory Transmission Out-of-paper Reception Fax Resolution Speed Dials Broadcasting Frax Features Handset	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S. Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 600 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Colon Optical: up to 600 x 1200 Enhanced: up to 1' - 24 Max 215.9mm x 300mm Scan to Email Windows®: TWAIN, WIA for Windows Vista®/Windows 10.8 x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 37C from ready mode 1% increments 0 99 1 copying (N=2,4) 11 copying (N=2,4) 12 copying (N=2,4) 13 copying (N=2,4) 14 copying (N=2,4) 15 copying (N=2,4) 16 copying (N=2,4) 17 copying (N=2,4) 18 copying (N=2,4) 19 copying (N=2,4) 10 copying (N=2,4) 10 copying (N=2,4) 11 copying (N=2,4) 12 copying (N=2,4) 13 copying (N=2,4) 14 copying (N=2,4) 15 copying (N=2,4) 16 copying (N=2,4) 17 copying (N=2,4) 17 copying (N=2,4) 18 copying (N=2,4) 19 copying (N=2,4) 19 copying (N=2,4) 10 copying (N=2,4) 10 copying (N=2,4) 10 copying (N=2,4) 10 copying (N=2,4) 11 copying (N=2,4) 11 copying (N=2,4) 11 copying (N=2,4) 11 copying (N=2,4) 12 copying (N=2,4) 13 copying (N=2,4) 14 copying (N=2,4) 15 copying (N=2,4) 16 copying (N=2,4) 17 copying (N=2,4) 17 copying (N=2,4) 18 copying (N=2,4) 18 copying (N=2,4) 19 copying (N=2,4) 10 copying (N=2,4) 10 copying (N=2,4) 10 copying (N=2,4) 11 copying (N=2,4) 12 copying (N=2,4) 13 copying (N=2,4) 14 copying (N=2,4) 15 copying (N=2,4) 16 copying (N=2,4) 17 copying (N=2,4) 17 copying (N=2,4) 18 copying (N=2,4
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	r, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S. Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS ^{IM} : Yes, WPS: Yes Up to 600 16 seconds or less at: 25 - 400% in Up t ID Card Copy, N ir Colon Optical: up to 600 x 1200 Enhanced: up to 1' - 24 Max 215.9mm x 300mm Scan to Email Windows®: TWAIN, WIA for Windows Vista®/Windows 10.8 x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) Irr CIS dpi (ffrom Scanner Glass), 2,200 x 19,200 dpi² Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege Folio I, Image, File² 8 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN 14.4 Kbps Up to 400 pages¹⁰ Up to 99 locations Up to 119 locations, Manual: 20 locations PC Fax Send and Receive (Windows only) Up to 2 hours
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modem Speed Memory Transmission Out-of-paper Reception Fax Resolution Speed Dials Broadcasting Fax Features Handset Handset Back-up Clock	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400 % in Up to 10 Optical: up to 600 x 1200 Enhanced: up to 11 - 24 Max 215.9mm x 300mm Scan to Emai Windows®: TWAIN, WIA for Windows Vista®/Window 10.8.x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) Irr CIS dpi (ffrom Scanner Glass), 2,200 x 19,200 dpi² Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege Folio I, Image, File² 8 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN 14.4 Kbps Up to 400 pages¹⁰ Up to 99 locations Up to 119 locations, Manual: 20 locations PC Fax Send and Receive (Windows only) Up to 2 hours
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Memory Transmission Out-of-paper Reception Fox Resolution Speed Dials Broadcasting Fox Features Handset Back-up Clock Warranty	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400 % in Up to 10 Optical: up to 600 x 1200 Enhanced: up to 11 - 24 Max 215.9mm x 300mm Scan to Emai Windows®: TWAIN, WIA for Windows Vista®/Window 10.8.x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) Irr CIS dpi (ffrom Scanner Glass), 2,200 x 19,200 dpi² Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege Folio I, Image, File² 8 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN 14.4 Kbps Up to 400 pages¹⁰ Up to 99 locations Up to 119 locations, Manual: 20 locations PC Fax Send and Receive (Windows only) Up to 2 hours
Wireless Network Security Wireless Network Setup Support Utility Copy Function Copy Speed (A4) Copy Resolution First-copy-out Time Reduction / Enlargement Multi-Copy Copy Feature Scan Function Type Scanning Resolution Colour Depth Document Size Scan Destinations Supported Driver Fax Function Compatibility Communication System Modem Speed Memory Transmission Out-of-paper Reception Fax Resolution Speed Dials Broadcasting Fax Features Handset Handset Back-up Clock	IPv6: NDP, RA, DNS Resolver, mDNS, LLMNR responde	er, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, S Client, I.CMP/6, Web Services (Print) Wireless: SMTP - AUTH WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES) AOSS TM : Yes, WPS: Yes Up to 60 16 seconds or less at: 25 - 400 % in Up to 10 Optical: up to 600 x 1200 Enhanced: up to 11 - 24 Max 215.9mm x 300mm Scan to Emai Windows®: TWAIN, WIA for Windows Vista®/Window 10.8.x	NMPv1/v2c, HTPP Server, TFTP Client and Server SMTP 10 cpm¹ x 600 dpi 23°C from ready mode % increments o 99 1 copying (N=2,4) Irr CIS dpi (ffrom Scanner Glass), 2,200 x 19,200 dpi² Optical: up to 600 x 600 dpi (from ADF) bit Platen: max 215.9mm x 300mm ADF: A4/Letter/Lege Folio I, Image, File² 8 7/Windows® 8.1; Mac: TWAIN/ICA for OS X v10.7.5, 10.9 x ITU-T G3 PSTN 14.4 Kbps Up to 400 pages¹⁰ Up to 99 locations Up to 119 locations, Manual: 20 locations PC Fax Send and Receive (Windows only) Up to 2 hours


¹ Print/copy speed may decrease due to factors such as paper type, paper size, and printing conditions. In periods of heavy duty printing or copying, the device may go into cool down mode. This safety feature protects the device from overheating, but will result in a temporary reduction in print or copy speed. ² Declared yield in accordance with ISO/IEC 19752. Yield will vary based on image area coverage and print mode. ³ Drum yield may vary by the type of use. ⁴ Windows Only. ⁵ Mac drivers are available by web download. ⁶ Max 1200 x 1200 at 1200 a

This product has been tested and found to comply with the Class 1 Laser Equipment requirements defined by the international standard IEC60825-1:2007 and has no light exposure hazard. The product has no hazardous light emission as it features light protection components and covers to shut in all light beam during operation and maintenance. Internal Laser radiation Wave length: 770 - 800 nm Output: 25 mW max. Laser Class: Class 3B

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law:

Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates. Unused postage stamps, post cards, etc.

Certificate stamps stipulated by law. Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.



Fuji Xerox Asia Pacific Pte Ltd

80 Anson Road #37-00 Fuji Xerox Towers Singapore 079907

Tel. +65-6766-8888

http://www.fxap.com.sg/

















For Your Safety
Before using the product, read the Instruction Manual carefully
for proper use. Use the product with the power source and voltage
specified. Be sure to establish ground connection. Otherwise,
electronic shock may result in the case of a failure or short circuit.

