

ECOSYS FS-C2626MFP / ECOSYS FS-C2526MFP A4 COLOUR MULTIFUNCTION PRINTERS

ECOSYS FS-C2626MFP / ECOSYS FS-C2526MFP



THE PROFESSIONAL WORKGROUP DEVICE FOR COLOUR IN A4

Speed and reliability in colour and monochrome is now combined with even higher usability to fulfill the growing demand of small and medium-sized workgroups. These highly productive devices with their integrated colour touch panel provide direct access to the full potential of the compact A4 MFP. The document workflow can be optimised with the use of dedicated program keys and the integrated solution platform HyPAS. The exceptional reliability of KYOCERA's long-life components makes them ideal for your business and good for the environment.

- ▶ Up to 26 pages per minute in A4 in colour and monochrome
- ▶ Double-sided print, copy, scan and fax* functionality as standard
- ▶ Powerful controller: 800MHz; 1GB RAM; Gigabit interface
- ▶ Up to 9,600 dpi printing quality with Multibit technology
- ▶ Full-colour touch panel provides ease of use
- ▶ High security through SSL, IPsec and Private Print functionality
- ▶ HyPAS solution platform enables powerful customisations
- ▶ Compact design with low noise
- ▶ Exceptionally low printing costs in its class

* Only ECOSYS FS-C2626MFP



 **KYOCERA**

we'll save you the Earth

ECOSYS FS-C2626MFP / ECOSYS FS-C2526MFP

A4 COLOUR MULTIFUNCTION PRINTERS

The ECOSYS FS-C2626MFP / ECOSYS FS-C2526MFP includes:

PRESCRIBE II

With the KYOCERA page design and control language PRESCRIBE II, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

For PRESCRIBE II compatibility, please call 13 KYOCERA (Aust) or 0508 KYOCERA (NZ)

The KM NetViewer

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Centre

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

HyPAS™ – Hybrid Platform for Advanced Solutions

KYOCERA's powerful software development platform enables users to customise the functionality and operations of the MFP to their individual requirements.



ECOSYS stands for ECOlogy, EConomy and SYStem-printing. With long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly and the drum unit every 200,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

General

Technology: KYOCERA ECOSYS Colour Laser, HyPAS solutions platform

Control panel display: 4.3 inch full-colour touch panel display

Engine speed: Up to 26 pages per minute in A4 in colour and monochrome

Resolution: 600 x 600 dpi
Multibit technology for print quality of up to 9,600 x 600 dpi

Warm-up time: Approx. 29 seconds or less from power on

Time to first print page:
Approx. 9 seconds or less in monochrome
Approx. 10.5 seconds or less in colour

Time to first print copy:
Approx. 10 seconds or less in monochrome
Approx. 12 seconds or less in colour

CPU: PowerPC 464 / 800MHz

Memory: Standard: 1024MB RAM
Max.: 2048MB RAM

Standard interfaces: USB 2.0 (Hi-Speed), USB Host 2.0 Host, FastEthernet (10/100/1000BaseTX)
Slot for optional internal print server
Slot for optional CompactFlash*-Card

Integrated accounting: 20 department codes

Dimensions (W x D x H): 514 mm x 550 mm x 603 mm

Weight: Approx. 38.7 kg (basic unit ready for operation)

Power source: 220~240 V, 50/60 Hz

Power consumption:	FS-C2526MF	FS-C2626MFP
Printing:	468 W	475 W
Copying:	465 W	469 W
Stand-by:	78 W	76 W
Sleep-mode:	14 W	16 W

Safety standards: GS / TÜV / CE
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard

Paper Handling

All paper capacities quoted are based on 80 gsm (paper thickness of max. 0.11 mm). Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray: 60 – 220 gsm; A4, A5, A6, B5, Letter, Legal, Folio, Envelopes, Custom (70 x 148 mm – 216 x 356 mm)

250-sheet universal cassette: 60 – 163 gsm; A4, A5, A6, B5, Letter, Legal, Folio, Custom (105 x 148 – 216 x 356 mm)

Max. paper capacity incl. options: 1,300 sheets

Duplex functionality: Double-sided printing: 60 – 163 gsm

Output capacity: 150 sheets face-down with paper full sensor

Print Functions

Controller language: PRESCRIBE II

Emulations: PCL6 (PCL5e, PCL-XL), PCL6 (PCL5c, PCL-XL), KPDL3, PDF Direct Printing V1.5 (Supported by KPDL3), XPS, Novell Print, IBM Proprinter X24E, EPSOM LQ-850, DIABLO 630

Operating systems: All current Windows operating systems, Mac OS X Version 10.2 or higher, UNIX, LINUX as well as other operating systems on request

Fonts/barcodes: 93 scalable fonts for PCL /PostScript*, 8 fonts for Windows Vista*, 1 bitmap font, 45 barcodes (e.g. EAN 8, EAN 13, EAN 128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

Features: Encrypted PDF Direct Print, IPP printing, email printing, WSD print, secure printing via SSL, IPsec, SNMPv3 and Private Print

Copy Functions

Max. original size: A4/Legal

Continuous copying: 1-999

Zoom range: 25-400% in 1% steps

Preset magnification ratios: 7 Reductions / 5 Enlargements

Exposure mode: Auto, manual: 7 steps

Image adjustments: Text, photo, mix, graphic/map, printer output

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

Scan Functions

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Network TWAIN, WSD (WIA) scan (USB, network)

Scan speed: 35 ipm (300 dpi, A4, monochrome), 25 ipm (600 dpi, A4 monochrome, 300 dpi, A4, colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales per colour)

Max. scan size: A4, Legal

Original recognition: Text, photo, text + photo, OCR

File types: TIFF, PDF, PDF/A, JPEG, XPS

Compression method: MMR/JPEG

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi-send (email, fax, SMB/FTP folder, print) at once

Fax Functions (FS-C2626MFP only)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: Less than 3 seconds

Scanning speed: 2.5 seconds

One-touch dial: 100 numbers

Address book: 200 entries

Scanning density:

Normal: 8 dot/mm x 3.85 line/mm

Fine: 8 dot/mm x 7.7 line/mm

Superfine: 8 dot/mm x 15.4 line/mm

Ultrafine: 16 dot/mm x 15.4 line/mm

Halftone: 256 greyscales

Maximum original size: A4, Legal

Compression method: JBIG, MMR, MR, MH

Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast 600, 400, 300, 200 dpi (256 greyscales per colour)

Consumables

Toner-Kit: TK-594C, TK-594M, TK-594Y: Average continuous cyan, magenta, yellow toner yield is 5,000 pages in accordance with ISO/IEC 19798

Toner-Kit: TK-594K: Average continuous black toner yield is 7,000 pages in accordance with ISO/IEC 19798

Average continuous starter toner yield is 3,500 pages (black) and 2,500 pages (cyan, magenta, yellow) in accordance with ISO/IEC 19798

Options

PF-520 Paper Feeder: 500 sheets; 60 – 163 gsm; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)

PF-530 Paper Feeder: 500 sheets; 60 – 220 gsm; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)

Up to 2 Paper Feeders can be attached, in any combination

Memory upgrade:

DIMM-1GBP: 1024MB

USB Flash Memory: Supports direct printing of PDF, XPS, TIFF, JPEG files via USB Host Interface

Optional interface

IB-50: Gigabit-Printserver 10BaseT/100BaseTX/1000BaseT

Warranty

2-year onsite warranty as standard. KYOCERA guarantees the drums and developers for 2 years or maximum 200,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions. Up to 4-year on-site warranty extension available.



The images displayed in this brochure are for illustrative purposes only, and may include optional extras.



we'll save you the Earth

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

Printed on Nordset, an environmentally responsible paper manufactured using Elemental Chlorine Free (ECF) pulp sourced from third party certified, well managed forests. Produced by Nordland Papier, a company certified under ISO14001 environmental management systems and registered under the EU Eco-management and Audit Scheme EMAS (Reg. No.D - 162 - 00007).

KYOCERA MITA Australia

Ph: 13 KYOCERA

www.kyoceramita.com.au

KYOCERA MITA New Zealand

Ph: 0508 KYOCERA

www.kyoceramita.co.nz

KYOCERA MITA Australia Pty Ltd ABN 77 003 852 444