## High Speed Office Mono Laser Printer

### Key Features
- Save time with fast 38ppm print speed and a first page out time of less 8.5 seconds (incorporating <1 second eco warm up)
- Automatic 2-Sided Print as Standard
- Less refilling with a 300 sheet paper capacity expandable to 800 sheets
- Hi-Speed USB 2.0, Built in Network and Wi-Fi N Connection
- Easy to use roam print features including with AirPrint, Google Cloud Print and WI-FI direct
- Keep print costs down with the High Yield Toner Option

### Supplies
Standard Yield Toner (TN-3330) Approx. 3,000 pages*
High Yield Toner (TN-3380) Approx. 8,000 pages*
Drum (DR-3300) Approx. 30,000 pages (one page per job)
*Approx. yield is declared in accordance with ISO/IEC 19752

### Optional Extras
- Optional 500 Lower Paper tray     LT5400 (Max 1)
- Additional 2 years warranty     ZWPS0130

**THE HL-5470DW IS A PROFESSIONAL PRINT PERFORMER OFFERING ENHANCED WORKGROUP CONNECTIVITY TO MEET THE MOST DEMANDING BUSINESS ENVIRONMENTS**

Regardless of your business size Brother understands that your business runs on information.

The HL-5470DW is packed with a range of easy-to-use, cost effective output solutions that are designed to deliver outstanding results time after time.

| | |
|---|---|
| Technology | Electrophotographic Laser Printer |
| Class 1 Laser Product | IEC 60825-1:2007 |
| Processor | StarSapphire 400MHz |
| Memory | 128MB (Expandable up to 384MB, using industry standard 1 x DDR2 16bit 144pin memory module) |
| LCD | 2 line, 16 digit back-lit LCD screen |
| Buttons | Go, Cancel, Secure, OK, Back, +, - |

| | |
|---|---|
| Print Speed – Standard (A4) | 38 pages per minute |
| Print Speed – Duplex (A4) | 18 sides per minute (9 sheets per minute) |
| Resolution | 1200 x 1200 dpi, HQ1200(2400 x 600 dpi), 600 x 600 dpi |
| First Print Out Time | Less than 8.5 seconds from ready mode |
| Warm-up Time | Less than 5 seconds from sleep mode |
| Print Language | PCL6, BR-Script3 (Postscript®3 Language Emulation), IBM Proprinter XL, Epson FX-850 |
| Embedded Fonts (PCL) | 66 scalable fonts, 12 bitmap fonts |
| Embedded Fonts (PS) | 66 scalable fonts |
| Embedded Barcodes (PCL) | Code39, Interleaved 2 of5, FIM(US-PostNet), Post Net(US-PostNet), EAN-8, EAN-13, UPC-A, UPC-E, Codabar, ISBN(EAN), ISBN(UPC-E), Code128(set A, set B, set C), EAN128(set A, set B, set C) |

| | |
|---|---|
| **Paper Input** | |
| Standard Tray: | 250 sheets |
| Multi-Purpose (MP) Tray: | 50 sheets |
| Optional Lower Tray: | 1 x 500 sheets (LT-5400) |
| **Paper Output** | |
| Face Down: | 150 sheets |
| Face Up (Straight Paper Path): | 1 sheet |
| **Media Types & Weights** | |
| Standard / Optional Tray: | Plain & recycled paper (between 60 - 105 g/m2 (16 - 28 lb)) |
| Multi-Purpose Tray: | Plain, recycled & bond paper (between 60 - 163g/m2 (16 to 43lb)) |
| Envelope Printing | Yes, from Multi-Purpose (MP) Tray (up to 3 at one time) |
| Label Printing | Yes, from Multi-Purpose (MP) Tray (accuracy & reliability will depend on the quality & type of labels used) |
| **Media Sizes** | |
| Standard / Optional Tray: | A4, Letter, B5(ISO/JIS), A5, A5(Long Edge), B6(ISO), A6, Executive, Legal, Folio (A4 only supported in automatic duplex print mode) |
| Multi-Purpose Tray: | Width: 76.2mm to 215.9mm (3" to 8.5") x Length: 127mm to 355.6mm (5" to 14") |

| | |
|---|---|
| Interfaces | Hi-Speed USB 2.0/ Wired Network (Network 10/100 Base-TX) & Wireless Network (IEEE 802.11b/g/n) |
| Network Protocols | TCP/IP (IPv4 and IPv6) |
| IPv4 | ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/ v3, ICMP, Web Services (Print), CIFS client, SNTP client () |
| IPv6 (off by default) | NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/v3, ICMPv6, Web Services (Print), CIFS Client, SNTP Client |
| Network Security | APOP, POP before SMTP, SMTP-AUTH, SSL/TLS (IPPS, HTTPS, SMTP, POP), SNMP v3, 802.1x (EAP-MD5, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), Kerberos |
| Wireless Setup Support | WiFi Protected Setup (WPS) & AirStation One-Touch Secure System  (AOSS) |
| Wi-Fi Direct | Intel My WiFi Technology & Vertical Pairing |
| Wireless Network Security | WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES), APOP, POP before SMTP, SMTP-AUTH, SSL/TLS (IPPS, HTTPS, SMTP, POP) |
| Enterprise Wireless Network Security | EAP-MD5, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS |

| | |
|---|---|
| **Printer Driver Features** | |
| Booklet Printing+ | Print documents in A5 booklet format using automatic or manual duplex print |
| Quite Mode | Reduces the noise of the machine whilst printing (a small reduction in print speed also occurs) |
| Skip Blank Page+ | Ignores any pages blank pages in your documents. |
| Toner Saving | This reduces the toner usage and helps to reduce the total cost of printer ownership |
| † Windows® only | |
| †† Windows® & Apple Macintosh only | |

| | |
|---|---|
| **Mobile/ Cloud Printing** | |
| iPrint&Scan (Android) 7 | Print JPG & PDF files directly from a smart phone or tablet running the Android Operating System |
| iPrint&Scan (iPad / iPhone / iPod) 7 | Print JPG & PDF files directly from an iPad / iPhone / iPod |
| Google Cloud Print | Print most common file types from any Google Cloud print enabled application |
| Apple AirPrint | Print most common file types from any Apple AirPrint enabled application |
| Cortado Cloud Print | Print most common file types from any smart phone, tablet or PC running Cortado applications that support Cortado Cloud Print |

| | |
|---|---|
| Compatible Operating Systems | Windows 7® (32 & 64 bit editions), Windows Vista® (32 & 64 bit editions), Windows® XP Professional (32 & 64 bit editions), Windows® XP Home Edition, Windows® Server 2008R2, Windows® Server 2008 (32 & 64 bit editions), Windows® Server 2003 (32 & 64 bit editions) - Mac OS X 10.5.8, 10.6.x, 10.7.x or greater - Linux CUPS, LPD/LPRng (x86/x64 environment)(Linux driver download only) |
| Recommended Monthly | 500 – 3,500 pages monthly print volume |

## Weights/ Dimensions/ Measures

With Carton  (WxDxH) 499 x 478 x 380 mm, 12.5 kg
W/ out Carton (WxDxH) 371 x 384 x 245 mm, 10.5 kg

| | Power Consumption (measured at 25ºC) | Sound Pressure Level | Sound Power Level |
|---|---|---|---|
| Active | Average 665W | Less than 59 dBA | Less than 6.79BA |
| Quiet Mode | Average 332W | Less than 54 dBA | Less than 6.4BA |
| Ready | Average 4.7W | Less than 34 dBA | Less than 4.7BA |
| Deep Sleep | Average 0.7W (2.8W when wireless Is active) | Inaudible | Inaudible |
| Auto Power Off (Off Mode) | Average 0.5W | Inaudible | Inaudible |
| TEC Value | 2.120kWh / Week | | |

## What's in the box

Toner Cartridge (Approx. 3,000 pages[1])
Drum Unit (Approx. 30,000 pages)
Power Supply Cord
Driver Software for Windows® and Mac
Quick Set-up Guide
PC Interface cable **NOT** included

Compatible with
Windows®7

CERTIFIED FOR
Windows
Vista®

Mac

Universal