Speed, productivity and low TCO

User-friendly, eco-friendly and cost-efficient, this device supports the print needs of busy offices. For larger workgroups, our space-saving designs can expand from a desktop model to a 45ppm, five tray floor standing powerhouse.

Boost your productivity

The fast CPU ensures the SP5200DN sprints into action: 7.5 seconds to first-page print out after warm up, and print at continuous speeds of 45 ppm. Easy paper handling saves time and helps make office life easier. With a 550-sheet input tray and a 100 sheet bypass tray as standard, these models also have the option to add on an additional four 550 sheet trays, meaning they can expand up to a maximum of a 2850-sheet input.

Well connected

The SP5200DN provides easy connection to your network with simple, time-saving driver installation. Full @Remote compatibility provides real-time remote support for performance monitoring and diagnosis management to boost efficiency. While our optional genuine IPDS™ module streamlines your print workflow for smooth document handling and minimised management costs.



High performance and feature packed

Highly productive and user friendly black & white laser printers.



Easy on the environment

Sustainability is a strong part of our heritage, and is a key element of every part of our company. From manufacturing to distribution, business sites to recycling. Maximising efficiency is a firm commitment, and that's why the SP5200DN is Energy Star compliant. Duplex printing, all-in-one toners and low power consumption also help to save energy and expense.



Automatic



GENERAL

Print speed: 45 ppm

Warm-up time: 20 sec or less

First print speed: 7.5 sec or less Duplex:

Dimensions (WxDxH): 411 x 435 x 400 mm

Weight: less than 23 kg

Power source: 220-240V, 50/60Hz

Power consumption: Max 1400W or less

Energy saver: 5W or less

CONTROLLER

Processor: 533 MHz

Resolution: up to 1200 x 600 dpi

Memory: 256 MB (Std) / 768 MB (Max)

HDD: 80GB (Std)

PCL5e/6, PostScript 3, Printer language:

IPDS (Option)

CONNECTIVITY

Interface: Ethernet 10BASE-T/100BASE-TX,

USB 20

TCP/IP (IPv4, IPv6), Apple Talk, Network protocol:

Bonjour, IPX/SPX (requires Netware option)

Supported

environments: Windows XP

> Windows Vista Windows Server 2003 Windows Server 2008

Windows 7

Mac OS (v10.2 or later)

Novell Netware (v6.5 or later) (Option)

Unix

SAP R/3 (3.x or later)

PAPER HANDLING

Paper input capacity (80 gsm):

Std. 550 sheets Bypass: 100 sheets 2850 sheets Max:

Paper output capacity: up to 500 sheets

A4 - A6 Paper size:

Paper weight: Std/Opt: 52 - 220 gsm

Bypass: 52 - 220 gsm

Duplex: 60 - 163 gsm

OTHER OPTIONS

HDD 80GB

550 sheet paper tray1

550 sheet paper tray with casters1

IPDS option

Netware print option

IEEE 802.11a/g interface unit

Gigabit Ethernet Board

IEEE 1284 Interface Unit

256 MB/512 MB memory option

VM Card

1. Please consult your local Lanier supplier for configuration options.

3YEAR WARRANTY

Lanier's award winning range of colour and black & white laser printers come with a standard three year on-site warranty. This sets a new industry benchmark in Australia. We are proud of our excellent reputation in customer service. You can feel confident that in the unlikely event that you encounter an issue, Lanier will quickly and easily rectify it. Our contact centre is available to assist you for the life of the printer's warranty and if an issue cannot be resolved over the phone. If an issue cannot be resolved over the phone, and depending

on where you're located, Lanier offers either a return to base (RTB) replacement with 'like for like' or onsite service



For more information please contact:







Lanier (Australia) Pty Ltd HEAD OFFICE 854 Lorimer Street | Port Melbourne | Victoria 3207

SYDNEY Branch Office 3 Chaplin Drive | Lane Cove | NSW 2066

BRISBANE Branch Office Unit 3/57Miller Street | MURARRIE | QLD 4172

PERTH Branch Office 19 Collingwood Street | Osborne Park | WA 6017

Lanier Customer Care: 1300 362 345 www.lanierprinters.com.au

