

NO FUSS PRINTING FOR QUALITY RESULTS

imageCLASS LBP841Cdn

WORKHORSE PLUS RANGE
– ADVANCE Colour Laser Printer



The imageCLASS LBP841Cdn incorporates everything you need from a printer and more. This reliable machine is perfect for smaller offices, delivering fast, professional results. Its cost-efficient features are also great for both the environment and your budget.

As with all models in Canon's new "LBP Advanced" range, the imageCLASS LBP841Cdn is built from the ground up to complement the existing printing environments of large businesses. It features integrated PCL, MEAP compatibility to allow the embedding of MEAP applications and compatibility with FM Audit & Print Fleet.

Key Features

MEAP-Embedded

With the embedded MEAP environment, users are able to utilise a range of MEAP applications, such as uniFLOW to enhance their workflows and increase productivity.

PCL Compatible

The LBP841Cdn supports PCL, making it ideal for use in large organisations with established print solutions.

Low Power Consumption and Quick Start Up

With Canon's unique On-Demand Fixing System, the LBP841Cdn achieves low power consumption of less than 22.5 watts (average) in standby and quick start-up, with first page out in less than 7.9 seconds. Canon's On-Demand Fixing System enables instantaneous heating of the fusing heater only before printing, saving warm-up time. The LBP841Cdn is always ready to print – saving you time and money.

Enhanced Security

Organisations can now eliminate unnecessary printing, while ensuring the security of sensitive documents with the LBP841Cdn's Secure Print features. This can be configured using the printer's memory for a server-less solution, or run via uniFLOW, which can be embedded onto the machine via MEAP.

eRDS capability

Direct access to e-Maintenance via eRDS, so there is no need for an EMAGENT or iWMC.



Excellent print speeds

With speeds of up to 26ppm, you can be confident you'll get what you need, when you need it.



Versatile media handling

Take control of page size, numbers and stock with ease.



Energy efficient

Standby and sleep modes allow for low power consumption and minimal impact on the environment.



Seamless network connectivity

Integrate with a wide range of business applications.



All-in-one cartridge system

Enjoy quality, cost efficient printouts with low maintenance.



Mobile printing solutions

Canon's PRINT Business app allows streamlined printing of everything from photos to web pages.

Canon

achieve more.

imageCLASS LBP841Cdn

Workhorse Plus Range – ADVANCE Colour Laser Printer

Print Specifications

Printing Method	Colour laser beam printing
Print Speed ¹	A4: 26 / 26ppm (mono / colour) A3: 15 / 15ppm (mono / colour)
Print Resolution	600 x 600 dpi, 1,200 x 1,200dpi, 9,600 (equivalent) x 600dpi
First Print Out Time (FPOT)	Approx. 7.9 / 9.9 seconds (mono / colour)
Print Language	UFR II, PCL6 (45 scalable fonts)
Warm-up Time (from power on)	29 seconds or less
Recovery Time (from sleep mode)	Approx. 9 seconds
Auto Duplex Printing	Standard
Available Paper Size for Auto Duplex Print	A3, B4, A4, B5, A5, Legal ¹ , Letter, Executiv, Foolscap

Paper Handling

Paper Input	Standard Casette: 250 sheets Multi-Purpose Tray: 100 sheets Maximum Paper Capacity: 2,000 sheets
Paper Output	250 sheets (face down)
Paper Size	Standard Casette: A3, B4, A4, B5, A5, Legal ¹ , Letter, Executive, Foolscap, Custom: width 148.0 to 297.0mm length 182.0 to 431.8mm Multi-Purpose Tray: A3, B4, A4, B5, A5, Legal ¹ , Letter, Executive, Foolscap, Index (3'x5'), Envelope: ISO-C5, No. 10, Monarch, DL Custom: width 76.2 to 304.8mm length 120.0 to 457.2mm
Paper Weight	Standard Casette - 60 to 128g/m ² Multi-Purpose Tray - 60 to 216g/m ²
Paper Type	Plain, Heavy, Label, Envelope

Connectivity & Software

Standard Interface	USB 2.0 High Speed 10Base-T / 100Base-TX / 1000Base-T
Network Interface	Supported protocol: TCP / IP (Frame type: Ethernet II), SMB (SMB is only available for LBP843Cx) Print application: LPD, RAW, IPP / IPPS, FTP, WSD
Mobile Print	Canon PRINT Business, Canon Print Service
Compatible Operating Systems	Windows [®] 10 (32 / 64-bit), Windows [®] 8.1 (32 / 64-bit), Windows [®] 8 (32 / 64-bit), Windows [®] 7 (32 / 64-bit), Windows [®] Vista (32 / 64-bit), Windows [®] Server 2012 (64-bit), Windows [®] Server 2008 R2 (64-bit), Windows [®] Server 2008 (32 / 64-bit), Windows [®] Server 2003 (32 / 64-bit), Mac OS [™] 10.6.8-, Linux ²


General Specifications

Device Memory	512MB
Operation Panel	5-line LCD Display
Dimensions (WxDxH)	545 x 591 x 361.2mm
Weight	Approx. 34kg
Power Consumption	Maximum: 1,420W or less During Operation: Approx. 530W During Standby: Approx. 22.5W During Sleep: Approx. 3W (USB connection), Approx 1.5W (Wired LAN connection)
Noise Level	During Operation: Sound Power: 6.68 or less, Sound Pressure: 51dB During Standby: Inaudible ⁴
Power Requirement	220 to 240V, 50 / 60Hz
Operating Environment	Temperature: 10 to 30°C Humidity: 20% to 80% RH (no condensation)
Toner Cartridge	CART335: yields 6,500 pages CART335L: yields 16,500 pages

Optional Accessories

Paper Feeder-E1	Paper Capacity: 550 sheets Paper Size: A3, B4, A4, B5, A5, Legal ¹ , Letter, Executive, Foolscap, Custom: width 148.0 to 297.0mm length 182.0 to 431.8mm Paper Weight: 60 to 128g/m ²
SD Card-C1	
Barcode Printing Kit-F1	
Waste Toner Box-722	

1. Legal refers to paper measuring 215.9 x 355.6mm (8.5 x 14 inches)
2. Optional paper feeder does not support 2-sided printing for A5 size.



LAS-2YOS-1 – 3 year Extended Onsite Service & Support card

canon.com.au/business

Follow us on Twitter @CanonBusinessAU

1800 444 199

4566-v1-07/16

Canon

achieve more.