

# ML184T+ DOT MATRIX PRINTER



## ❖❖❖ ML184T+ ❖❖❖ 9-PIN DOT MATRIX PRINTER

### **THE RELIABLE AND AFFORDABLE PRINTER FOR INDUSTRIAL AND POINT OF SALE APPLICATIONS**

As the entry level printer in the Oki 9-pin dot matrix range, the ML184T+ is fast and robust, yet compact and light. A true demand document printer with bottom feed and short tear, its special size makes it ideal for customer service environments and industrial workstation applications.

### **MAIN FEATURES OF THE ML184T+ PRINTER**

- ❖❖❖ Compact 80 column dot matrix printer
- ❖❖❖ Oki's unique, high durability 9-pin print head
- ❖❖❖ Multi-part continuous forms handling (original + 3 copies)
- ❖❖❖ Up to 375 characters per second print speed
- ❖❖❖ Ideal for data logging, label printing and point of sale use
- ❖❖❖ Suited to harsh environments
- ❖❖❖ DC version also available for remote or mobile use



# OKI

# ML184T+ DOT MATRIX PRINTER

## PRODUCT SPECIFICATION

|                                    |   | ML184T+   | ML184T+ DC     |
|------------------------------------|---|---|----------------|
| <b>General</b>                     | Number of pins                          | 9   |                |
|                                    | No. of multi-part forms                 | 4 (one original + 3 copies)   |                |
| <b>Speed &amp; throughput</b>      | Super speed draft (12cpi only)          | 375cps  | 300cps         |
|                                    | High speed draft (all cpi)              | 333cps  | 240cps         |
|                                    | Utility (all cpi)                       | 250cps  | 200cps         |
|                                    | Near letter quality (all cpi)           | 62.5cps   | 50cps          |
|                                    | Fastest print speed                     | 375cps  | 300cps         |
| <b>Font &amp; print features</b>   | Carriage width (10cpi)                  | 80 columns  |                |
|                                    | Max. in compressed mode                 | 160 columns   |                |
|                                    | Character pitch                         | 10/12/15/17.1/20 pitch  |                |
|                                    | Graphics resolution                     | Up to 240 x 216 dpi   |                |
|                                    | Typeface & Font                         | Utility, High Speed Draft, NLQ, Barcodes                                  |                |
|                                    | Typestyle                               | Emphasised, Enhanced, Double Width, Italics                               |                |
| <b>Emulations &amp; interfaces</b> | Printer emulations                      | Epson LX, IBM Graphics or Oki MicroLine                                   |                |
|                                    | Standard interfaces                     | Centronics Parallel, USB  |                |
|                                    | Optional interfaces                     | Serial RS 232C/RS 422/Current Loop  |                |
| <b>Paper handling</b>              | Continuous paper                        | 76.2 – 241.3mm  |                |
|                                    | First printable line (from top of page) | Cut sheet: 15mm<br>Continuous: 16.9mm                                     |                |
|                                    | Standard                                | Autoload single sheet, Platen pin feed, Low tear-off, Paper end detection |                |
|                                    | Optional                                | Roll paper stand, Pull tractor feed, Single bin sheet feeder              |                |
| <b>Physical</b>                    | Dimensions (HxWxD)                      | 80 x 372 x 275mm  |                |
|                                    | Weight                                  | 4.5kg   | 4.0kg          |
|                                    | Memory                                  | 128KB   |                |
|                                    | Noise level                             | 51dB (quiet mode)   |                |
| <b>Power</b>                       | Power requirements                      | 220V-240V AC  | 9.6 – 31.2V DC |
|                                    | Frequency                               | 50/60Hz   |                |
| <b>Reliability</b>                 | Print head life                         | 200 million characters  |                |
|                                    | Ribbon life                             | 3 million characters (re-inking cartridge)                                |                |
| <b>Supplies life</b>               | MTBF                                    | 20,000 hours  |                |

# OKI

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

Okī, Network Solutions  
for a Global Society

IPL DATRON PTY LTD  
63-85 VICTORIA STREET  
ALEXANDRIA NSW 2015  
AUSTRALIA  
TEL: (02) 9690 8200  
FAX: (02) 9690 8300  
[WWW.OKI.COM.AU](http://WWW.OKI.COM.AU)



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency



Oki is proud to sponsor the Oki European Challenge - 2005. For more information visit [WWW.OKIEUROCHALLENGE.COM](http://WWW.OKIEUROCHALLENGE.COM)